



WOYR8.E42363 - Switches, Appliance and Special Use Certified for Canada - Component

Switches, Appliance and Special Use Certified for Canada - Component

See General Information for Switches, Appliance and Special Use Certified for Canada - Component

C & K COMPONENTS INC

1601 Trapelo Rd, Ste 178
Waltham, MA 02451 USA

Investigated to CAN/CSA-C22.2 No. 61058-1

E42363

Cat. No.	Load	Amps	Volts	Hz	Temp (°C)	Pol/ Thr/ Cir	Endurance		Dis IP	(mm)	SPCA	Std. Ed.
							30C cycle	55C cycle				
Appliance Switches												
PT series PT f/b 101,102,103,105,107 or 108. f/b S. f/b S,Q or Z. f/b Q. f/b 00												
	GP	15	277	50/60	T85	1/M-1.2	6K	10K	66	full 1.6	-	-
	GP	15(4)	277	50/60	T85	1/M-1.2	6K	10K	66			
	hp	1/2	125	50/60	T85	1/M-1.2	6K	10K	66			
	hp	1	250	50/60	T85	1/M-1.2	6K	10K	66			
	GP	10	277	50/60	T85	1/M-1.2	6K	10K	66			
	GP	10(4)	277	50/60	T85	1/M-1.2	6K	10K	66			
	hp	1/4	125	50/60	T85	1/M-1.2	6K	10K	66			
	hp	1/2	250	50/60	T85	1/M-1.2	6K	10K	66			
Micro												
LCA-01 f/b 150; f/b A05, P00, S06, S09, T05, T06, T09, T12, T16, T18, T21, T23, T36, T43; f/b R, L, P, Q, or S; f/b C,W, or Y, may be f/b letters or numbers.												
	R	0.1	125-250	60	T125	1/2-2.2	6K	10K	--	micro	Notes 6, 11,12,13	-
LCA-06 f/b 150; f/b A05, P00, S06, S09, T05, T06, T09, T12, T16, T18, T21, T23, T36, T43; f/b R, L, P, Q, or S; f/b C,W, or Y, may be f/b letters or numbers.												
	R	6	125-250	60	T125	1/2-2.2	6K	10K	--	micro	Notes 6, 11,12,13	-
LCA-10 f/b 150; f/b A05, P00, S06, S09, T05, T06, T09, T12, T16, T18, T21, T23, T36, T43; f/b R, L, P, Q, or S; f/b C,W, or Y, may be f/b letters or numbers.												

	GP	10.1	125-250	60	T125	1/2-2.2	6K	10K	--	micro	Notes 6, 11,12,13	-
LCA-S5 f/b 150; f/b A05, P00, S06, S09, T05, T06, T09, T12, T16, T18, T21, T23, T36, T43; f/b L, P, Q, or S; f/b C,W, or Y, may be f/b letters or numbers.												
	R	5	125-250	50-60	T55	1/2-2.2	6K	100K	--	micro	Note 6, 13	-
	GP	5	125-250	50-60	T55	1/2-2.2	6K	10K	--			
LCS-01 f/b [M1] ;[M1]=[1 or 2, f/b A05, P00, S26, T00, T05, T07, T13, T19, T28, or T43, f/b S, or Q f/b C, W, or Y, may be f/b letters or numbers]												
	R	0.1	125	60	T120	1/1 or 1/2-2.2	6K	10K	--	micro	Note 6,11,14,15,22	-
	R	0.1	250	60	T120	1/1 or 1/2-2.2	6K	10K	--			
	R	0.1	30	DC	T120	1/1 or 1/2-2.2	6K	10K	--			
	R	0.1	125	60	T55	1/1 or 1/2-2.2	6K	10K	--			
	R	0.1	250	60	T55	1/1 or 1/2-2.2	6K	10K	--			
	R	0.1	30	DC	T55	1/1 or 1/2-2.2	6K	10K	--			
LCS-01 f/b [M2] ;[M2]=[1 or 2, f/b A05, P00, S26, T00, T05, T07, T13, T19, T28, or T43, f/b P, W, or Z, may be f/b A, B, C, or D, f/b, 20, 22, 24, 26, 28 or 30, may be f/b A, B, C, D, or E, f/b C, W, or Y, may be f/b letters or numbers]												
	R	0.1	125	60	T55	1/1 or 1/2-2.2	6K	10K	--	micro	Note 6,11,14,15,22	-
	R	0.1	125	60	T55	1/1 or 1/2-2.2	6K	10K	--			
	R	0.1	250	60	T55	1/1 or 1/2-2.2	6K	10K	--			
	R	0.1	250	60	T55	1/1 or 1/2-2.2	6K	10K	--			
	R	0.1	30	DC	T55	1/1 or 1/2-2.2	6K	10K	--			
	R	0.1	30	DC	T55	1/1 or 1/2-2.2	6K	10K	--			
LCS-05 f/b 1 or 2, f/b A05, P00, S26, T00, T05, T07, T13, T19, T28, or T43, f/b P, W, or Z, may be f/b A, B, C, or D, f/b, 20, 22, 24, 26, 28 or 30, may be f/b A, B, C, D, or E, f/b C, W, or Y, may be f/b letters or numbers.												
	R	5	125	60	T55	1/1 or 1/2-2.2	6K	10K	66	micro	Note 6,11,14,15,22	2009-08-10
	R	5	250	60	T55	1/1 or 1/2-2.2	6K	10K	66			

	R	5	30	DC	T55	1/1 or 1/2-2.2	6K	10K	66			
	GP	5	250	60	T55	1/1 or 1/2-2.2	6K	10K	66			
	GP	5	125	60	T55	1/1 or 1/2-2.2	6K	10K	66			
	R	5	125	60	T55	1/1 or 1/2-2.2	6K	10K	67			
	R	5	250	60	T55	1/1 or 1/2-2.2	6K	10K	67			
	R	5	30	DC	T55	1/1 or 1/2-2.2	6K	10K	67			
	GP	5	250	60	T55	1/1 or 1/2-2.2	6K	10K	67			
	GP	5	125	60	T55	1/1 or 1/2-2.2	6K	10K	67			
LCS-05 f/b 1 or 2, f/b A05, P00, S26, T00, T05, T07, T13, T19, T28, or T43, f/b S, or Q f/b C, W, or Y, may be f/b letters or numbers.												
	R	5	125	60	T120	1/1 or 1/2-2.2	6K	10K	--	micro	Note 6,11,14,15,22	-
	R	5	250	60	T120	1/1 or 1/2-2.2	6K	10K	--			
	R	5	30	DC	T120	1/1 or 1/2-2.2	6K	10K	--			
	GP	5	250	60	T120	1/1 or 1/2-2.2	6K	10K	--			
	GP	5	125	60	T120	1/1 or 1/2-2.2	6K	10K	--			
	R	5	125	60	T55	1/1 or 1/2-2.2	6K	10K	--			
	R	5	250	60	T55	1/1 or 1/2-2.2	6K	10K	--			
	R	5	30	DC	T55	1/1 or 1/2-2.2	6K	10K	--			
	GP	5	250	60	T55	1/1 or 1/2-2.2	6K	10K	--			
LCV6	RM	5(2)	250	50-60	T85	1/M-1.2	6K	10K	00	micro	-	2009- 08-10
	GP	5	250	50-60	T85	1/M-1.2	6K	10K	00			
	R	5	30	DC	T85	1/M-1.2	6K	10K	00			
	hp	1/3	125- 250	50-60	T85	1/M-1.2	6K	10K	00			

LCV7	RM	10(2)	250	50-60	T85	1/M-1.2	6K	10K	00	micro	-	2009-08-10
	GP	10	250	50-60	T85	1/M-1.2	6K	10K	00			
	R	10	30	DC	T85	1/M-1.2	6K	10K	00			
	hp	1/3	125-250	50-60	T85	1/M-1.2	6K	10K	00			
LCX1	GP	1	250	50-60	T85	1/M-1.2	6K	25K	00	micro	-	2009-08-10
	R	1	30	DC	T85	1/M-1.2	6K	10K	00			
TF2 f/b [M1] ;[M1]=[CC, CF, CG, CH , CJ, or EC, f/b H8, f/b S or V, f/b P00, A10, A15, A20, A25, T10, T14, T15, T16, T17, T20, T24, T25, T26, or T27, f/b 4A, 4B, 10, 40, or 60, f/b C, W, or Y, may be f/b letters or numbers]												
	R	6	125-250	50-60	T55	1/1,1/2-1.2, 2.2	6K	10K	--	micro	3B,12,15	-
	R	6	125-250	50-60	T85	1/1,1/2-1.2, 2.2	6K	10K	--			
	R	6	125-250	50-60	T125	1/1,1/2-1.2, 2.2	6K	10K	--			
TF2 f/b [M2] ;[M2]=[CH , CJ, EC, or EE, f/b J6, f/b S or V, f/b P00, A10, A15, A20, A25, T10, T14, T15, T16, T17, T20, T24, T25, T26, or T27, f/b 4A, 4B, 10, 40, or 60, f/b C, W, or Y, may be f/b letters or numbers]												
	R	16	125-250	50-60	T55	1/1,1/2-1.2, 2.2	6K	10K	--	micro	3B,12,15	-
	R	16	125-250	50-60	T85	1/1,1/2-1.2, 2.2	6K	10K	--			
	R	16	125-250	50-60	T125	1/1,1/2-1.2, 2.2	6K	10K	--			
	GP	16	125-250	50-60	T55	1/1,1/2-1.2, 2.2	6K	10K	--			
	GP	16	125-250	50-60	T85	1/1,1/2-1.2, 2.2	6K	10K	--			
	GP	16	125-250	50-60	T125	1/1,1/2-1.2, 2.2	6K	10K	--			
	hp	1/2	125-250	50-60	T55	1/1,1/2-1.2, 2.2	6K	10K	--			
TF2 f/b [M3] ;[M3]=[CH , CJ, EC, or EE, f/b K6, f/b S or V, f/b P00, A10, A15, A20, A25, T10, T14, T15, T16, T17, T20, T24, T25, T26, or T27, f/b 4A, 4B, 10, 40, or 60, f/b C, W, or Y, may be f/b letters or numbers]												
	R	10	125-250	50-60	T55	1/1,1/2-1.2, 2.2	6K	10K	--	micro	3B,12,15	-
	R	10	125-250	50-60	T85	1/1,1/2-1.2, 2.2	6K	10K	--			
	R	10	125-250	50-60	T125	1/1,1/2-1.2, 2.2	6K	10K	--			

TF2 f/b [M4] ;[M4]=[CC, CF, CG, CH , CJ, EC, or EE, f/b F5, f/b S or V, f/b P00, A10, A15, A20, A25, T10, T14, T15, T16, T17, T20, T24, T25, T26, or T27, f/b 4A, 4B, 10, 40, or 60, f/b C, W, or Y, may be f/b letters or numbers]

	R	0.1	125-250	50-60	125	1/1, 1/2-2.2	6K	10K	--	micro	3B,12,15	-
	R	0.1	125-250	50-60	85	1/1, 1/2-2.2	6K	10K	--			
	R	0.1	125-250	50-60	55	1/1, 1/2-2.2	6K	10K	--			

TF3, f/b 10, 16, 20, 25, f/b CJ, EK, CG, EE, CF or EC f/b P00, T10, T15, T30, T24, A10, A15 or any letters and numbers, f/b 40, 4A or any letters and numbers , f/b Y, may be f/b letters or numbers.

	R	25.1	250	60	125	1/1 or 1/2-1.2	6K	10K	--	full 3.2	-	-
	R	10	250	60	125	1/1 or 1/2-1.2	6K	10K	--			
	R	16	250	60	125	1/1 or 1/2-1.2	6K	10K	--			
	R	20	250	60	125	1/1 or 1/2-1.2	6K	10K	--			
	RM	16(4)	125-250	50-60	125	1/1 or 1/2-1.2	6K	10K	--			
	RM	10.1(8)	125-250	50-60	125	1/1 or 1/2-1.2	6K	10K	--			
	hp	1/2	125-250	60	100	1/1 or 1/2-1.2	6K	-	--			
	hp	1	125-250	60	100	1/1 or 1/2-1.2	6K	-	--			

TFS-01 f/b S, D, J, L, or H, f/b P00, T10, T20, A05, A10, A20, or A25, f/b 40, or W, f/b C, Y, or W, may be f/b C, D, E, F, G, or H, may be f/b B, f/b S or None, may be f/b letters or numbers.

	R	0.1	250	60	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--	micro	Notes 16, 17, 18	-
	R	0.1	125	60	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	0.1	30	DC	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	0.1	125	60	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	0.1	250	60	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			

	R	0.1	30	DC	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
TFS-03 f/b S, D, J, L, or H, f/b P00, T10, T20, A05, A10, A20, or A25, f/b 40, or W, f/b C, Y, or W, may be f/b C, D, E, F, G, or H, may be f/b B, f/b S or None, may be f/b letters or numbers.												
	R	3	250	60	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--	micro	Notes 16, 17, 18	-
	R	3	125	60	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	3	30	DC	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	3	125	60	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	3	250	60	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	3	30	DC	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
TFS-06 f/b S, D, J, L, or H, f/b P00, T10, T20, A05, A10, A20, or A25, f/b 40, or W, f/b C, Y, or W, may be f/b C, D, E, F, G, or H, may be f/b B, f/b S or None, may be f/b letters or numbers.												
	R	6	250	60	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--	micro	Notes 16, 17, 18	-
	R	6	125	60	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	6	30	DC	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	6	125	60	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	6	250	60	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	6	30	DC	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
TFS-10 f/b S, D, J, L, or H, f/b P00, T10, T20, A05, A10, A20, or A25, f/b 40, or W, f/b C, Y, or W, may be f/b C, D, E, F, G, or H, may be f/b B, f/b S or None, may be f/b letters or numbers.												

	R	10	250	60	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--	micro	Notes 16, 17, 18	-
	R	10	125	60	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	5	30	DC	T85	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	10	125	60	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	10	250	60	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
	R	5	30	DC	T55	1/2 or 1/1-2.2 or 1.2	6K	10K	--			
<p>ZMA f/b 00A or G00 f/b 150 or 080, f/b P00, S03, L30, L21, L11, L08, A03, L04, S06, S07 or S08, f/b P, L, R, E, or K, may be f/b by C, may be f/b letters or numbers.</p>												
	R	0.1	60	DC	T55	1/2-2.2	6K	10K	--	micro	6,7	-
	R	0.1	24	DC	T55	1/2-2.2	6K	10K	--			
	R	0.1	125	50-60	T55	1/2-2.2	6K	10K	--			
	R	0.1	250	50-60	T55	1/2-2.2	6K	10K	--			
<p>ZMA f/b 01A or G01 f/b 150 or 080, f/b P00, S03, L30, L21, L11, L08, A03, L04, S06, S07 or S08, f/b P, L, R, E, or K, may be f/b by C, may be f/b letters or numbers.</p>												
	R	1	24	DC	T55	1/2-2.2	6K	10K	--	micro	6,7	-
	R	1	125	50-60	T55	1/2-2.2	6K	10K	--			
	R	1	250	50-60	T55	1/2-2.2	6K	10K	--			
<p>ZMA f/b 03A or G03 f/b 150 or 080, f/b P00, S03, L30, L21, L11, L08, A03, L04, S06, S07 or S08, f/b P, L, R, E, or K, may be f/b by C, may be f/b letters or numbers.</p>												
	R	3	125	60	T55	1/2-2.2	6K	10K	--	micro	6,7	-
	R	3	24	DC	T55	1/2-2.2	6K	10K	--			
	R	1	125	50-60	T55	1/2-2.2	6K	10K	--			
	R	1	125	50-60	T55	1/2-2.2	6K	10K	--			
	R	1	250	50-60	T55	1/2-2.2	6K	10K	--			
<p>ZMS f/b [M1] ;[M1]=[H or L, f/b 00 or 03, f/b 130, f/b P00, T10, or T11, f/b P, L, R, or S f/b S, L, R or M, f/b C, W, or Y, may be f/b letters or numbers]</p>												
	R	3	125	60	T55	1/2 or 1/1-2.2	6K	10K	--	micro	Notes 7A, 7B, 7C	-

	R	3	12	DC	T55	1/2 or 1/1-2.2	6K	100K	--			
	R	0.1	12	DC	T55	1/2 or 1/1-2.2	6K	100K	--			
	R	0.01	12	DC	T55	1/2 or 1/1-2.2	6K	100K	--			

ZMS f/b [M2] ;[M2]=[H or L, f/b 00 or 03, f/b 130, f/b P00, T10, or T11, f/ J, K, or W, f/b S, L, R or M, f/b C, W, or Y, may be f/b letters or numbers]

	R	3	125	60	T55	1/2 or 1/1-2.2	6K	10K	--	micro	Notes 7A, 7B, 7C	-
	R	3	12	DC	T55	1/2 or 1/1-2.2	6K	100K	--			
	R	0.1	12	DC	T55	1/2 or 1/1-2.2	6K	100K	--			
	R	0.01	12	DC	T55	1/2 or 1/1-2.2	6K	100K	--			

ZMSM f/b H or L, f/b 0 or 3, f/b 130, f/b P00, T10, T11, f/b P, S, J, K, W, or N, f/b M, L, R, T, or F, f/b C, W, or Y, may be f/b letters or numbers.

	R	3	125	60	T55	1/2 or 1/1-2.2	6K	10K	--	micro	Notes 7A, 7B, 7C	-
	R	3	12	DC	T55	1/2 or 1/1-2.2	6K	100K	--			
	R	0.1	12	DC	T55	1/2 or 1/1-2.2	6K	100K	--			
	R	0.01	12	DC	T55	1/2 or 1/1-2.2	6K	100K	--			

Push Button

DS1 f/b [M3] ;[M3]=[D6, f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank]

	GPM	10(4)	250	50-60	T85	1/1-1.2	6K	50K	--	full 1.6	Note 3A, 3B	-
	GPM	10(4)	125	50-60	T85	1/1-1.2	6K	50K	--			
	RM	10(4)	250	50-60	T85	1/1-1.2	6K	50K	--			
	RM	10(4)	125	50-60	T85	1/1-1.2	6K	50K	--			
	GP	10	250	50-60	T85	1/1-1.2	6K	50K	--			
	GP	10	125	50-60	T85	1/1-1.2	6K	50K	--			
	hp	1/3	250	50-60	T85	1/1-1.2	6K	50K	--			
	hp	1/3	125	50-60	T85	1/1-1.2	6K	50K	--			

DS1, f/b D7, f/b A or B, f/b Q3, f/b BK or blank.

	RM	16(6)	250	50-60	T85	1/1-1.2	0K	10K	40	full 1.6	Note 4A, 4B, 23	2009-08-10
--	----	-------	-----	-------	-----	---------	----	-----	----	----------	-----------------	------------

	RM	16(6)	125	50-60	T85	1/1-1.2	0K	10K	40			
	GP	16	250	50-60	T85	1/1-1.2	0K	10K	40			
	GP	16	125	50-60	T85	1/1-1.2	0K	10K	40			
	hp	3/4	250	50-60	T85	1/1-1.2	6K	10K	40			
	hp	3/4	125	50-60	T85	1/1-1.2	0K	10K	40			
DS1F5 f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank												
	GPM	0.5(0.5)	125-250	50-60	T85	1/1-1.2	6K	50K	40	full 1.6	Note 3A, 3B	-
	RM	0.1(0.5)	125-250	50-60	T85	1/1-1.2	6K	50K	40			
	GP	0.1	125-250	50-60	T85	1/1-1.2	6K	50K	40			
DS1F7 f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank												
	GPM	0.5(0.5)	125-250	50-60	T85	1/1-1.2	6K	100K	40	full 1.6	Note 3A, 3B	-
	RM	0.1(0.5)	125-250	50-60	T85	1/1-1.2	6K	100K	40			
	GP	0.1	125-250	50-60	T85	1/1-1.2	6K	100K	40			
DS2 f/b [M3] ;[M3]=[D6, f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank]												
	RM	10(4) PP	250	50-60	T85	2/1-1.5	6K	50K	--	full 1.6	Note 3A, 3B	-
	RM	10(4) PP	125	50-60	T85	2/1-1.5	6K	50K	--			
	GP	10 PP	250	50-60	T85	2/1-1.5	6K	10K	--			
	GP	10 PP	125	50-60	T85	2/1-1.5	6K	10K	--			
	hp	1/3 PP	250	50-60	T85	2/1-1.5	6K	10K	--			
	hp	1/3 PP	125	50-60	T85	2/1-1.5	6K	10K	--			
DS2, f/b D7, f/b A or B, f/b Q3, f/b BK or blank.												
	RM	16(6) PP	250	50-60	T85	2/1-1.5	0K	10K	40	full 1.6	Note 3A, 3B, 23	2009-08-10
	RM	16(6) PP	125	50-60	T85	2/1-1.5	0K	10K	40			
	GP	16 PP	250	50-60	T85	2/1-1.5	0K	10K	40			
	GP	16 PP	125	50-60	T85	2/1-1.5	0K	10K	40			
	hp	3/4 PP	250	50-60	T85	2/1-1.5	6K	10K	40			
	hp	3/4 PP	125	50-60	T85	2/1-1.5	0K	10K	40			
DS2F5 f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank												

	GPM	0.5(0.5) PP	125- 250	50-60	T85	2/1-1.5	6K	50K	40	full 1.6	Note 3A, 3B	-
	RM	0.1(0.5) PP	125- 250	50-60	T85/55	2/1-1.5	6K	50K	40			
	GP	0.1 PP	125- 250	50-60	T85	2/1-1.5	6K	50K	40			
DS2F7 f/b A, B, C, D or E, f/b Q1, Q2, Q3, Q4, Q5, Q6, Q7 or Q8, f/b BK or blank												
	GPM	0.5(0.5) PP	125- 250	50-60	T85	2/1-1.5	6K	100K	40	full 1.6	Note 3A, 3B	-
	RM	0.1(0.5) PP	125- 250	50-60	T85	2/1-1.5	6K	100K	40			
	GP	0.1 PP	125- 250	50-60	T85	2/1-1.5	6K	100K	40			
NE18 f/b 2A or 2U, f/b blank or 2U, f/b EE or OA, f/b blank or SN, f/b blank, P or L, f/b 4AMP or 6AMP												
	GP	8	125	50-60	T70	M/M-1.2	6K	10K	00	full 2	21	-
	GP	8	125	50-60	T70	M/M-1.3	6K	10K	00			
	GP	6	250	50-60	T70	M/M-1.2	6K	10K	00			
	GP	6	250	50-60	T70	M/M-1.3	6K	10K	00			
	RM	6(4)	250	50-60	T70	M/M-1.2	6K	10K	00			
	RM	6(4)	250	50-60	T70	M/M-1.3	6K	10K	00			
	RC	6(48)	250	50-60	T70	M/M-1.2	6K	10K	00			
	RC	6(48)	250	50-60	T70	M/M-1.3	6K	10K	00			
	R	1	100	DC	T70	M/M-1.2	6K	10K	00			
	R	1	100	DC	T70	M/M-1.3	6K	10K	00			
	R	8	30	DC	T70	M/M-1.2	6K	10K	00			
	R	8	30	DC	T70	M/M-1.3	6K	10K	00			
NE18CTII f/b 2A or 2U, f/b blank or 2U, f/b EE or OA, f/b blank or SN, f/b blank, P or L, f/b 4AMP or 6AMP												
	GP	4	250	50-60	T70	M/M-1.2	6K	10K	00	full 2	21	-
	GP	4	250	50-60	T70	M/M-1.3	6K	10K	00			
	RC	4(48)	250	50-60	T70	M/M-1.2	6K	10K	00			
	RC	4(48)	250	50-60	T70	M/M-1.3	6K	10K	00			
	R	1	100	DC	T70	M/M-1.2	6K	10K	00			
	R	1	100	DC	T70	M/M-1.3	6K	10K	00			
	R	4	30	DC	T70	M/M-1.2	6K	10K	00			
	R	4	30	DC	T70	M/M-1.3	6K	10K	00			
Reed Type Switch, magnetically actuated, Mechanical type												

MPS45WGW	R	0.1	50	50-60	75	1/1-1.2	6K	100K	40	micro	A	2005-09-30
	R	0.1	50	DC	75	1/1-1.2	6K	100K	40			
	R	0.25	20	50-60	75	1/1-1.2	6K	100K	40			
	R	0.25	20	DC	75	1/1-1.2	6K	100K	40			
Rocker												
CG101-xx-x-xx-xx-x-xx-x												
	RM	16(4)	125-250	50-60	T85/55	1/2-3.2	6K	10K	--	full 1.5	12, 16A, 16B, 16D	-
	R	16	12	DC	T85/55	1/2-3.2	6K	10K	--			
	R	10	28	DC	T85/55	1/2-3.2	6K	10K	--			
	RM	16(4)	125-250	50-60	85	1/2-3.2	6K	10K	--			
	R	16	12	DC	85	1/2-3.2	6K	10K	--			
	R	10	28	DC	85	1/2-3.2	6K	10K	--			
CG102-J2-x-xx-xx-x-xx-x												
	RM	16(4)	125-250	50-60	T85/55	1/2-3.2	6K	10K	--	full 1.5	12, 16A, 16B, 16D	-
	R	16	12	DC	T85/55	1/2-3.2	6K	10K	--			
	R	10	28	DC	T85/55	1/2-3.2	6K	10K	--			
	RM	16(4)	125-250	50-60	85	1/2-3.2	6K	10K	--			
	R	16	12	DC	85	1/2-3.2	6K	10K	--			
	R	10	28	DC	85	1/2-3.2	6K	10K	--			
CG103-xx-x-xx-xx-x-xx-x												
	RM	16(4)	125-250	50-60	T85/55	1/2-3.2	6K	10K	--	full 1.5	12, 16A, 16B, 16D	-
	R	16	12	DC	T85/55	1/2-3.2	6K	10K	--			
	R	10	28	DC	T85/55	1/2-3.2	6K	10K	--			
	RM	16(4)	125-250	50-60	85	1/2-3.2	6K	10K	--			
	R	16	12	DC	85	1/2-3.2	6K	10K	--			
	R	10	28	DC	85	1/2-3.2	6K	10K	--			
CG105-xx-x-xx-xx-x-xx-x												
	RM	16(4)	125-250	50-60	T85/55	1/2-3.2	6K	10K	--	full 1.5	12, 16A, 16B, 16D	-
	R	16	12	DC	T85/55	1/2-3.2	6K	10K	--			

	R	10	28	DC	T85/55	1/2-3.2	6K	10K	--			
	RM	16(4)	125-250	50-60	85	1/2-3.2	6K	10K	--			
	R	16	12	DC	85	1/2-3.2	6K	10K	--			
	R	10	28	DC	85	1/2-3.2	6K	10K	--			
CG12-J3-x-xx-xx-x-xx-x												
	RM	16(4)	125-250	50-60	T85/55	1/2-3.2	6K	10K	--	full 1.5	12, 16A, 16B, 16D	-
	R	16	12	DC	T85/55	1/2-3.2	6K	10K	--			
	R	10	28	DC	T85/55	1/2-3.2	6K	10K	--			
	RM	16(4)	125-250	50-60	85	1/2-3.2	6K	10K	--			
	R	16	12	DC	85	1/2-3.2	6K	10K	--			
	R	10	28	DC	85	1/2-3.2	6K	10K	--			
CR101-xx-x-xx-xx-Q												
	RM	10(4)	125,250	50-60	85	1/2-3.2	6K	10K	40	full 2	2A,2B,2C,2D	2009-08-10
CR102-J3-x-xx-xx-xx-x												
	RM	10(4)	125,250	50-60	85	1/1-2.2	6K	10K	--	full 2	2A,2B,2C,2D	-
CR102-J5-x-xx-xx-xx-x												
	RM	10(4)	125,250	50-60	85	1/1-2.2	6K	10K	--	full 2	2A,2B,2C,2D	-
CR102-JP-x-xx-xx-xx-x												
	RM	10(4)	125,250	50-60	85	1/1-2.2	6K	10K	--	full 2	2A,2B,2C,2D	-
CR102-xx-x-xx-xx-xx-x												
	RM	10(4)	125,250	50-60	85	1/1-2.2	6K	10K	--	full 2	2A,2B,2C,2D	-
CR103-xx-x-xx-xx-xx-x												
	RM	10(4)	125,250	50-60	85	1/2-3.2	6K	10K	40	full 1.5	2A, 2B, 2C, 2D	2009-08-10
D101, D102, D103, D105, D108, D201, D202, D203												
	GP	4	125	50-60	85	M/M-1.2, 1.3	6K	10K	00	full 2.5	-	2009-08-10
	GP	2	250	50-60	85	M/M-1.2, 1.3	6K	10K	00			
	R	4	30	DC	85	M/M-1.2, 1.3	6K	10K	00			
	RM	4(2)	125	50-60	85	M/M-1.2, 1.3	6K	10K	00			

	RM	2(1)	250	50-60	85	M/M-1.2, 1.3	6K	10K	00			
D501, D502, D503, D508, D601, D602, D608												
	GP	10	125	50-60	85	M/M-1.2, 1.3	6K	10K	00	full 2.5	-	2009-08-10
	GP	5	250	50-60	85	M/M-1.2, 1.3	6K	10K	00			
	R	10	30	DC	85	M/M-1.2, 1.3	6K	10K	00			
	RM	10(6)	125	50-60	85	M/M-1.2, 1.3	6K	10K	00			
	RM	5(3)	250	50-60	85	M/M-1.2, 1.3	6K	10K	00			
DA101-xx-x-xx-xx-x-xx-x												
	RM	16(4)	250	50-60	T85	1/2-2.2	6K	10K	40	full 2.2	Notes 11A, 11B, 11C	2009-08-10
	RM	16(4)	250	50-60	T85/55	1/2-2.2	6K	10K	40			
	RM	16(4)	125	50-60	T85	1/2-2.2	6K	10K	40			
	RM	16(4)	125	50-60	T85/55	1/2-2.2	6K	10K	40			
	R	16	12	DC	T85	1/2-2.2	6K	10K	40			
	R	16	12	DC	T85/55	1/2-2.2	6K	10K	40			
	R	6	28	DC	T85	1/2-2.2	6K	10K	40			
	R	6	28	DC	T85/55	1/2-2.2	6K	10K	40			
DA102-J3-x-xx-xx-x-xx-x, DA102-J4-x-xx-xx-x-xx-x												
	RM	16(4)	250	50-60	T85	1/1-1.2	6K	10K	40	full 2	Notes 11A, 11B, 11C	2009-08-10
	RM	16(4)	250	50-60	T85/55	1/1-1.2	6K	10K	40			
	RM	16(4)	125	50-60	T85	1/1-1.2	6K	10K	40			
	RM	16(4)	125	50-60	T85/55	1/1-1.2	6K	10K	40			
	R	16	12	DC	T85	1/1-1.2	6K	10K	40			
	R	16	12	DC	T85/55	1/1-1.2	6K	10K	40			
	R	6	28	DC	T85	1/1-1.2	6K	10K	40			
	R	6	28	DC	T85/55	1/1-1.2	6K	10K	40			
DA102-J5-x-xx-xx-x-xx-x												
	RM	16(4)	250	50-60	T85	1/1-1.2	6K	10K	40	full 1.8	Notes 11A, 11B, 11C	2009-08-10
	RM	16(4)	250	50-60	T85/55	1/1-1.2	6K	10K	40			

	RM	16(4)	125	50-60	T85	1/1-1.2	6K	10K	40			
	RM	16(4)	125	50-60	T85/55	1/1-1.2	6K	10K	40			
	R	16	12	DC	T85	1/1-1.2	6K	10K	40			
	R	16	12	DC	T85/55	1/1-1.2	6K	10K	40			
	R	6	28	DC	T85	1/1-1.2	6K	10K	40			
	R	6	28	DC	T85/55	1/1-1.2	6K	10K	40			
DA102-xx-x-xx-xx-x-xx-x												
	RM	16(4)	250	50-60	T85	1/1-1.2	6K	10K	40	full 2.4	Notes 11A, 11B, 11C	2009-08-10
	RM	16(4)	250	50-60	T85/55	1/1-1.2	6K	10K	40			
	RM	16(4)	125	50-60	T85	1/1-1.2	6K	10K	40			
	RM	16(4)	125	50-60	T85/55	1/1-1.2	6K	10K	40			
	R	16	12	DC	T85	1/1-1.2	6K	10K	40			
	R	16	12	DC	T85/55	1/1-1.2	6K	10K	40			
	R	6	28	DC	T85	1/1-1.2	6K	10K	40			
	R	6	28	DC	T85/55	1/1-1.2	6K	10K	40			
DA103-xx-x-xx-xx-x-xx-x												
	RM	16(4)	250	50-60	T85	1/2-3.2	6K	10K	40	full 1.5	Notes 11A, 11B, 11C	2009-08-10
	RM	16(4)	250	50-60	T85/55	1/2-3.2	6K	10K	40			
	RM	16(4)	125	50-60	T85	1/2-3.2	6K	10K	40			
	RM	16(4)	125	50-60	T85/55	1/2-3.2	6K	10K	40			
	R	16	12	DC	T85	1/2-3.2	6K	10K	40			
	R	16	12	DC	T85/55	1/2-3.2	6K	10K	40			
	R	6	28	DC	T85	1/2-3.2	6K	10K	40			
	R	6	28	DC	T85/55	1/2-3.2	6K	10K	40			
DM21, DM22, DM14, DM24												
	GP	3	125	50-60	85	M/M-1.2, 1.3	6K	10K	00	full 2.5	-	2009-08-10
	GP	2	250	50-60	85	M/M-1.2, 1.3	6K	10K	00			
	R	3	30	DC	85	M/M-1.2, 1.3	6K	10K	00			
DM61, DM62, DM54, DM64												
	GP	10	125	50-60	85	M/M-1.2, 1.3	6K	10K	00	full 2.5	-	2009-08-10

	GP	5	250	50-60	85	M/M-1.2, 1.3	6K	10K	00			
	R	10	30	DC	85	M/M-1.2, 1.3	6K	10K	00			
SW-1 f/b [M1] ;[M1]=[1, 2 or 3; f/b A, f/b 10; f/b F or N; f/b -A, -B, -C, -D, -E, -F, -G, -H, -BR, -CR, -DR, -ER, -FR, -GR or -HR; f/b 02, 03, 04, 05, 06, 07, 08, 09, 10, 11 or 12; f/b number(s) or blank for color]												
	GP	10	250	50-60	T85/55	1/1 or 1/2-1.2,2.2,or	6K	10K	--	full 1.6	Note 1B, 1C, 6	-
	GP	10	125	50-60	T85/55	1/1 or 1/2-1.2,2.2,or	6K	10K	--			
	RM	10(8)	250	50-60	T85/55	1/1 or 1/2-1.2,2.2,or	6K	10K	--			
	RM	10(8)	125	50-60	T85/55	1/1 or 1/2-1.2,2.2,or	6K	10K	--			
	RM	6(4)	250	50-60	T85/55	1/1 or 1/2-1.2,2.2,or	6K	50K	--			
	RM	6(4)	125	50-60	T85/55	1/1 or 1/2-1.2,2.2,or	6K	50K	--			
	hp	3/4	250	50-60	T85/55	1/1 or 1/2-1.2,2.2,or	6K	10K	--			
	hp	1/3	125	50-60	T85/55	1/1 or 1/2-1.2,2.2,or	6K	10K	--			
SW-1 f/b [M2] ;[M2]=[1, 2 or 3; f/b A, f/b 06; f/b F or N; f/b -A, -B, -C, -D, -E, -F, -G, -H, -BR, -CR, -DR, -ER, -FR, -GR or -HR; f/b 02, 03, 04, 05, 06, 07, 08, 09, 10, 11 or 12; f/b number(s) or blank for color]												
	GPM	6(2)	250	50-60	T85/55	1/1 or 1/2-1.2, 2.2 o	6K	10K	--	full 1.6	Note 1B, 1C, 6	-
	GPM	6(2)	125	50-60	T85/55	1/1 or 1/2-1.2, 2.2 o	6K	10K	--			
	RM	6(2)	250	50-60	T85/55	1/1 or 1/2-1.2, 2.2 o	6K	10K	--			
	RM	6(2)	125	50-60	T85/55	1/1 or 1/2-1.2, 2.2 o	6K	10K	--			
	GP	-	-	-	-	-	-	-	--			

	GP	6	250	50-60	T85/55	1/1 or 1/2-1.2, 2.2 o	6K	10K	--			
	GP	6	125	50-60	T85/55	1/1 or 1/2-1.2, 2.2 o	6K	10K	--			
	R	6	250	50-60	T85/55	1/1 or 1/2-1.2, 2.2 o	6K	10K	--			
	R	6	125	50-60	T85/55	1/1 or 1/2-1.2, 2.2 o	6K	10K	--			

SW-2 f/b [M1] ;[M1]=[1 or 6; f/b A; f/b 16; f/b N; f/b -A, -B, -C, -D, -ER, -CR or -FR; f/b 02, 03, 04, 05, 06, 07, 08, 09, 10, 11, 12, 13, 15 or 16; f/b number(s) or blank for color]



	R	16	250	50-60	T85	1/1 or 2/1-1.2 or 1.4	-	10K	--	full 1.7	Notes 1B, 1C, 6	-
	R	16	250	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	-	10K	--			
	R	16	125	50-60	T85	1/1 or 2/1-1.2 or 1.4	-	10K	--			
	R	16	125	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	-	10K	--			
	hp	3/4	250	50-60	T85	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	hp	3/4	250	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	hp	1/2	125	50-60	T85	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	hp	1/2	125	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	6K	10K	--			

SW-2 f/b [M2] ;[M2]=[1 or 6; f/b A; f/b 10; f/b N; f/b -A, -B, -C, -D, -ER, -CR or -FR; f/b 02, 03, 04, 05, 06, 07, 08, 09, 10, 11, 12, 13, 15 or 16; f/b number(s) or blank for color]

	RM	10(4)	250	50-60	T85	1/1 or 2/1-1.2 or 1.4	6K	50K	--	full 1.7	Notes 1B, 1C, 6	-
	RM	10(4)	250	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	6K	50K	--			

	RM	10(4)	125	50-60	T85	1/1 or 2/1-1.2 or 1.4	6K	50K	--			
	RM	10(4)	125	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	6K	50K	--			
	I	10	250	50-60	T85	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	I	10	250	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	I	10	125	50-60	T85	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	I	10	125	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	RC	8	250	50-60	T85	1/1 or 2/1-1.2 or 1.3	6K	10K	--			
	RC	8	250	50-60	T85/55	1/1 or 2/1-1.2 or 1.3	6K	10K	--			
	RC	8	125	50-60	T85	1/1 or 2/1-1.2 or 1.3	6K	10K	--			
	RC	8	125	50-60	T85/55	1/1 or 2/1-1.2 or 1.3	6K	10K	--			
	hp	1/2	250	50-60	T85	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	hp	1/2	250	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	hp	1/3	125	50-60	T85	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
	hp	1/3	125	50-60	T85/55	1/1 or 2/1-1.2 or 1.4	6K	10K	--			
Rocker												
9201	GP	6 PP	125	50-60	85	2/2-2.5	6K	10K	00	full 3.5	Note 20	2009- 08-10
	GP	3 PP	250	50-60	85	2/2-2.5	6K	10K	00			

	R	6 PP	30	DC	85	2/2-2.5	6K	10K	00			
Slide												
V701	GP	10	125	50-60	85	1/1-1.2	6K	10K	00	full 4.4	-	2009-08-10
	GP	5	250	50-60	85	1/1-1.2	6K	10K	00			
	RM	2(0.5)	250	50-60	85	1/1-1.2	6K	10K	00			
	R	4	30	DC	85	1/1-1.2	6K	10K	00			
V702	GP	10	125	50-60	85	1/2-1.2	6K	10K	00	full 4.4	-	2009-08-10
	GP	5	250	50-60	85	1/2-1.2	6K	10K	00			
	RM	2(0.5)	250	50-60	85	1/2-1.2	6K	10K	00			
	R	4	30	DC	85	1/2-1.2	6K	10K	00			
V801	GP	10	125	50-60	85	2/1-1.3	6K	10K	00	full 4.4	-	2009-08-10
	GP	5	250	50-60	85	2/1-1.3	6K	10K	00			
	RM	2(0.5)	250	50-60	85	2/1-1.3	6K	10K	00			
	R	4	30	DC	85	2/1-1.3	6K	10K	00			
V802	GP	10	125	50-60	85	2/2-1.3	6K	10K	00	full 4.4	-	2009-08-10
	GP	5	250	50-60	85	2/2-1.3	6K	10K	00			
	RM	2(0.5)	250	50-60	85	2/2-1.3	6K	10K	00			
	R	4	30	DC	85	2/2-1.3	6K	10K	00			
Toggle												
9121 and 9122	GP	10	125	50-60	85	1/M-1.2	6K	10K	00	full 3.5	Note 20	2009-08-10
	GP	5	250	50-60	85	1/M-1.2	6K	10K	00			
	R	13	60	DC	85	1/M-1.2	6K	10K	00			
	R	22	36	DC	85	1/M-1.2	6K	10K	00			
9221	GP	10 PP	125	50-60	85	2/2-2.5	6K	10K	00	full 3.5	Note 20	2009-08-10
	GP	5 PP	250	50-60	85	2/2-2.5	6K	10K	00			
	R	10 PP	30	DC	85	2/2-2.5	6K	10K	00			

Marking: Company name or tradename "C & K Unimax", "P/", "PRIME SOURCE", "PS", "PSL" or trademark  PrimeSource, catalog, model or part number, electrical ratings and the Recognized Component Mark for Canada,  on the product or on the smallest unit container in which the product is packaged.

Investigated to CSA-C22.2 No. 55

Cat. No.	Amps	Volts	Hz	Load	Endur- ance	Temp C	POL/ THR	Per Pole/ Circuit Code	SPCOA
,MXU w/suffixes SBX,SXX w/suff. 24HB w/suffixes (F6)									
	1	125	60	GP	100K	150	M/M	-/-	-
1 w/wo suffixes f/b TM w/wo suffixes Ratings: E2									
	5	250	60	GP	6K	150	1/M	-/-	-
	2	480	60	GP	6K				
1 w/wo suffixes f/b TM w/wo suffixes Ratings: U66									
	5	250	60	GP	6K	150	1/M	-/-	-
	-	125- 250	60	1/6hp	6K				
1101,1103,1108,1201,1203 all w/wo suff.									
	6	125	60	GP	6K	65	M/2	-/-	-
	3	250	60	GP	6K				
2 w/wo suffixes f/b TM w/wo suffixes f/b U Ratings: U34									
	10	125	60	GP	100K	150	1/M	-/-	-
	10	250	60	GP	100K				
	-	125	60	1/3hp	100K				
	-	250	60	1/3hp	100K				
2, 6 w/wo suffixes f/b TM w/wo suffixes Ratings: E2									
	5	250	60	GP	6K	150	1/M	-/-	-
	2	480	60	GP	6K				
2, 6 w/wo suffixes f/b TM w/wo suffixes Ratings: E3									
	5	250	60	GP	6K	150	1/M	-/-	-
2, 6 w/wo suffixes f/b TM w/wo suffixes Ratings: U33									
	10	125	60	GP	6K	150	1/M	-/-	-
	10	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
	0.5	125	DC	-	6K				
	0.25	250	DC	-	6K				
2, 6 w/wo suffixes f/b TM w/wo suffixes Ratings: U34									
	10	125	60	GP	6K	150	1/M	-/-	-

	10	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
22HB w/wo suffixes f/b "U13" "U13" = 100K wo U=6K									
	-	125-250	-	GP	100K	150	M/M	-/-	-
22HB w/wo suffixes f/b "U18" "U18" = 100K wo U=6K									
	-	125-250	-	GP	100K	150	M/M	-/-	-
22HB w/wo suffixes f/b "U2" "U2" = 100K wo U=6K									
	-	125-250	-	GP	100K	150	M/M	-/-	-
22HB w/wo suffixes f/b "U39" "U39" = 100K wo U=6K									
	-	250	-	GP	100K	150	M/M	-/-	-
3 w/wo suffixes f/b TM w/wo suffixes f/b U Rating: U31									
	15	125	60	GP	100K	150	1/M	-/-	-
	15	250	60	GP	100K				
	-	125	60	1/2hp	100K				
	-	250	60	1/2hp	100K				
3 w/wo suffixes f/b TM w/wo suffixes Ratings: F5									
	1	125	60	GP	6K	150	1/M	-/-	-
	1	30	DC	-	6K				
3 w/wo suffixes f/b TM w/wo suffixes Ratings: F6									
	1	125	60	GP	6K	150	1/M	-/-	-
3 w/wo suffixes f/b TM w/wo suffixes Ratings: U30									
	15	125	60	GP	6K	150	1/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	1/2hp	6K				
	-	250	60	1/2hp	6K				
	0.5	125	DC	-	6K				
	0.25	250	DC	-	6K				
3 w/wo suffixes f/b TM w/wo suffixes Ratings: U31									
	15	125	60	GP	6K	150	1/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	1/2hp	6K				

	-	250	60	1/2hp	6K				
3 w/wo suffixes f/b TM w/wo suffixes Ratings: U43									
	15	250	60	GP	6K	150	1/M	-/-	-
3 w/wo suffixes f/b TM w/wo suffixes Ratings: U60									
	15	125	60	GP	6K	150	1/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	1/2hp	6K				
	-	250	60	1/2hp	6K				
	0.5	125	DC	-	6K				
	0.25	250	DC	-	6K				
3 w/wo suffixes f/b TM w/wo suffixes Ratings: U61									
	15	125	60	GP	6K	150	1/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	1/2hp	6K				
	-	250	60	1/2hp	6K				
	3	125	60	L	6K				
3 w/wo suffixes f/b TM w/wo suffixes Ratings: U62									
	15	250	60	GP	6K	150	1/M	-/-	-
	3	125	60	L	6K				
3 w/wo suffixes f/b TM w/wo suffixes Ratings: U95									
	-	-	-	GP	6K	150	1/M	-/-	-
71,72,81,82	11	125-250	60	GP	6K	65	M/M	PP/-	-
7154 w/wo suff.	6	120	60	GP	6K	105	M/M	-/-	-
	2	250	60	GP	6K				
	2	48	DC	-	6K				
8161,8168,8261 all w/wo suff.									
	6	120	60	GP	6K	65	M/2	PP/-	-
	3	250	60	GP	6K				
853 f/b 1-4 w/wo suff.	1	120	60	GP	6K	65	1/1	-/-	-
	1	28	DC	-	6K				
8551 and 8552 w/wo suff.	3	120	60	GP	6K	65	1/1	-/-	-
	3	28	DC	-	6K				

8631 and 8632 w/wo suffixes									
	0.5	120	60	GP	6K	65	1/1	-/-	-
9201 all w/wo suff.	6	125	60	GP	6K	65	2/2	-/-	-
	3	250	60	GP	6K				
9221 all w/wo suff.	10	125	60	GP	6K	65	2/2	-/-	-
	5	250	60	GP	6K				
A f/b 1,2,3,4 f/b 01-99 w/wo suff., N f/b 5,6,7,8 f/b 00, 01, 16, 41 w/wo suff.									
	2.5	125	60	GP	6K	65	M/M	PP/-	Note 3
	0.35	125	DC	-	6K				
	1	250	50/60	GP	6K				
A800 to A899 w/wo 0-9 w/wo U w/wo suffixes and/or prefix Ratings: C2 (a)									
	15	125	60	GP	6K	150	M/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	3/4hp	6K				
	-	250	60	1- 1/2hp	6K				
	2	48	DC	-	100K				
A800 to A899 w/wo 0-9 w/wo U w/wo suffixes and/or prefix Ratings: C6 (a)									
	25	125	60	GP	6K	150	M/M	-/-	-
	25	250	60	GP	6K				
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				
	2	48	DC	-	100K				
A800 to A899 w/wo 0-9 w/wo U w/wo suffixes and/or prefix Ratings: E1 (a)									
	25	125	60	GP	6K	150	M/M	-/-	-
	25	250	60	GP	6K				
	-	125	60	3/4hp	6K				
	-	250	60	1- 1/2hp	6K				
A800 to A899 w/wo 0-9 w/wo U w/wo suffixes and/or prefix Ratings: F1 (a)									
	12	250	50/60	GP	6K	150	M/M	-/-	-
	-	125	50/60	1/2hp	6K				
	-	250	50/60	1hp	6K				
	2	48	DC	-	100K				

A800 to A899 w/wo 0-9 w/wo U w/wo suffixes and/or prefix Ratings: J5 (a)									
	25	250	60	GP	6K	150	M/M	-/-	-
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				
AD f/b GG, KH, PD, PF f/b L2 w/wo prefix and/or suffix letters and/or numbers									
	10	250	60	GP	6K	150	M/M	-/-	-
	-	125	60	1/2hp	-				
	-	250	60	1hp	-				
	2	48	DC	-	100K				
Any Recognized Switch w/CW									
	3	120	60	GP	6K	65	1/2	-/-	-
AQ34A-W Rating: C2	15	125	60	GP	6K	150	1/1	-/-	Note 4
	15	250	60	GP	6K				
	-	125	60	3/4hp	6K				
	-	250	60	1- 1/2hp	6K				
	2	48	DC	-	100K				
AS f/b GG, KH, PD, PF f/b L2 w/wo prefix and/or suffix letters and/or numbers									
	10	250	60	GP	6K	150	M/M	-/-	-
	-	125	60	1/2hp	-				
	-	250	60	1hp	-				
	2	48	DC	-	100K				
AS, AD f/b GG, KH, PD, PF f/b A2 w/wo prefix and/or suffix letters and/or numbers									
	5	125- 250	60	GP	6K	150	M/M	-/-	-
AS, AD f/b GG, KH, PD, PF f/b B8 w/wo prefix and/or suffix letters and/or numbers									
	15	125	60	GP	6K	150	M/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	1/2hp	6K				
	-	250	60	1hp	6K				
AS, AD f/b GG, KH, PD, PF f/b C2 w/wo prefix and/or suffix letters and/or numbers									
	15	125	60	GP	6K	150	M/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	3/4hp	6K				

	-	250	60	1- 1/2hp	6K				
AS, AD f/b GG, KH, PD, PF f/b C6 w/wo prefix and/or suffix letters and/or numbers									
	25	125	60	GP	6K	150	M/M	-/-	-
	25	250	60	GP	6K				
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				
AS, AD f/b GG, KH, PD, PF f/b E1 w/wo prefix and/or suffix letters and/or numbers									
	25	125	60	GP	6K	150	M/M	-/-	-
	25	250	60	GP	6K				
	-	125	60	3/4hp	6K				
	-	250	60	1- 1/2hp	6K				
AS, AD f/b GG, KH, PD, PF f/b F1 w/wo prefix and/or suffix letters and/or numbers									
	12	250	50/60	GP	6K	150	M/M	-/-	-
	-	125	50/60	1/2hp	6K				
	-	250	50/60	1hp	6K				
AS, AD f/b GG, KH, PD, PF f/b F3 w/wo prefix and/or suffix letters and/or numbers									
	25	125	60	GP	6K	150	M/M	-/-	-
	25	250	60	GP	6K				
	2	24	DC	-	6K				
AS, AD f/b GG, KH, PD, PF f/b F5 w/wo prefix and/or suffix letters and/or numbers									
	1	125	60	GP	6K	150	M/M	-/-	-
	1	30	DC	-	6K				
AS, AD f/b GG, KH, PD, PF f/b F6 w/wo prefix and/or suffix letters and/or numbers									
	1	125	60	GP	6K	150	M/M	-/-	-
AS, AD f/b GG, KH, PD, PF f/b L8 w/wo prefix and/or suffix letters and/or numbers									
	30	277	60	GP	6K	150	M/M	-/-	-
	-	125	60	1hp	-				
	-	250	60	2hp	-				
ATP19 Series	3	125- 250	50/60	R	50K	65	2/2	-/A,B	Note 2
ATP22 Series	3	125- 250	50/60	R	50K	65	2/2	-/A,B	Note 2

ATP25 Series	3	125-250	50/60	R	50K	65	2/2	-/A,B	Note 2
B or L f/b 1,2 f/b 0-3 f/b 1-4 w/wo suffixes									
	4	125	60	GP	6K	65	M/M	PP/-	-
	2	250	60	GP	6K				
	0.5	125	DC	-	6K				
C101, C102 w/wo suffixes	10	125	60	GP	6K	65	1/M	-/-	-
	7.5	250	60	GP	6K				
C121,C122,C221,C222	15	125	50/60	GP	6K	65	M/M	PP/-	-
	10	250	50/60	GP	6K				
C5170	5	125	60	GP	6K	65	1/M	-/-	-
	5	250	60	GP	6K				
CA f/b 01,02,04,21,22 or 24 f/b J1,f/b additional suffixes									
	15	125	60	GP	6K	65	M/M	PP/-	-
	10	250	60	GP	6K				
	-	125-250	60	1/4hp	6K				
CA-C5174	15	125	60	GP	6K	65	1/M	-/-	-
	10	250	60	GP	6K				
	-	125-250	60	1/4hp	6K				
CG-102-J1-x-xx-xx-x-xx-x	20	125	60	GP	6K	85	1/1 or 1/2	-/A	Note 2
	16	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/2hp	6K				
CG101-xx-x-xx-xx-x-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				
CG102-J2-x-xx-xx-x-xx-x	20	125	60	GP	6K	85	1/1 or 1/2	-/A	Note 2
	16	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/2hp	6K				
CG103-xx-x-xx-xx-x-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				

CG105-xx-x-xx-xx-x-xx-x	20	125	60	GP	6K	85	1/1 or 1/2	-/A	Note 2
	16	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/2hp	6K				
CG12-J3-x-xx-xx-x-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				
CL101-xx-x-xx-xx-x-xx-x	16	125	60	GP	6K	85	1/1 or 1/2	-/A	Note 12
	10	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/2hp	6K				
CL102-xx-x-xx-xx-x-xx-x	16	125	60	GP	6K	85	1/1 or 1/2	-/A	Note 12
	10	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/2hp	6K				
CL102-xx-x-xx-xx-x-xx-x, CL12-J9-x-xx-xx-x-xx-x, CL101-xx-x-xx-xx-x-xx-x									
	16	125	60	GP	6K	85	1/1 or 1/2	-/A	Note 12
	10	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/2hp	6K				
CL12-J9-x-xx-xx-x-xx-x	16	125	60	GP	6K	85	1/1 or 1/2	-/A	Note 12
	10	250	60	GP	6K				
CM101-xx-x-xx-xx-x-xx-x	16	125	60	1/8hp	6K	-	M/2	-/-	-
	10	250	60	1/3hp	6K				
CM102-xx-x-xx-xx-x-xx-x	16	125	60	1/8hp	6K	-	-	-/-	-
	10	250	60	1/3hp	6K				
CM103-xx-x-xx-xx-x-xx-x	16	125	60	1/8hp	6K	-	-	-/-	-
	10	250	60	1/3hp	6K				
CM107-xx-x-xx-xx-x-xx-x	16	125	60	1/8hp	6K	-	-	-/-	-

	10	250	60	1/3hp	6K				
CM12-J3-x-xx-xx-x-xx-x	16	125	60	1/8hp	6K	85	M/M	PP/-	2, Note 2
	10	250	60	1/3hp	6K				
CN201-J6-x-xx-xx-x-xx-x	16	125	60	1/8hp	6K	85	M/M	PP/-	2, Note 2
	10	250	60	1/3hp	6K				
CN201-xx-x-xx-xx-x-xx-x	16	125	60	1/3hp	6K	65	2/M	PP/-	2, Note 5
	10	250	60	1/2hp	6K				
CN202-J1-x-xx-xx-x-xx-x	16	125	60	1/3hp	6K	65	2/M	PP/-	2, Note 5
	10	250	60	1/2hp	6K				
CN202-J6-x-xx-xx-x-xx-x	16	125	60	1/8hp	6K	85	M/M	PP/-	2, Note 2
	10	250	60	1/3hp	6K				
CN22-J3-x-xx-xx-x-xx-x	16	125	60	1/3hp	6K	65	2/M	PP/-	2, Note 5
	10	250	60	1/2hp	6K				
CN22-J8-x-xx-xx-x-xx-x	16	125	60	1/8hp	6K	85	M/M	PP/-	2, Note 2
	10	250	60	1/3hp	6K				
CR101-xx-x-xx-xx-x-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				
CR102-J3-x-xx-xx-x-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				
CR102-J4-x-xx-xx-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				
CR102-J5-x-xx-xx-x-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				
CR102-JP-x-xx-xx-x-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				
CR102-xx-x-xx-xx-x-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				
CR103-xx-x-xx-xx-x-xx-x	16	125	60	GP	-	-	-	-/-	-
	10	250	60	GP	-				

D101 or 902504101	4	125	60	GP	6K	65	M/M	-/-	-
	2	250	60	GP	6K				
D102 or 902504102	4	125	60	GP	6K	65	M/M	-/-	-
	2	250	60	GP	6K				
D103,902504103	4	125	60	GP	6K	65	1/M	-/-	3
	2	250	60	GP	6K				
D105 or 902504105	4	125	60	GP	6K	65	M/M	-/-	-
	2	250	60	GP	6K				
D108 or 902504108	4	125	60	GP	6K	65	M/M	-/-	-
	2	250	60	GP	6K				
D151 or 902504151,D152 or 902504152									
	4	125	60	GP	6K	105	M/M	-/-	-
	2	250	60	GP	6K				
D201 or 902504201w/suffixes									
	2	250	60	GP	6K	65	M/M	-/-	-
D202 or 902504202 w/suffixes									
	2	250	60	GP	6K	65	M/M	-/-	-
D203,902504203	4	125	60	GP	6K	65	2/M	PP/-	-
	2	250	60	GP	6K				
D501 or 902504501 w/suffixes									
	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
D502 or 902504502 w/suffixes									
	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
D503,902504503	10	125	60	GP	6K	65	1/M	-/-	3
	5	250	60	GP	6K				
D508 or 902504508 w/suffixes									
	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
D601 or 902504601 w/suffixes									
	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				

D602 or 902504602w/suffixes									
	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
D603,902504603	10	125	60	GP	6K	65	2/M	PP/-	-
	5	250	60	GP	6K				
DA w/wo suff. w/wo prefixes Ratings: A2									
	5	125	60	GP	6K	150	2/M	-/-	-
	5	250	60	GP	6K				
DA w/wo suff. w/wo prefixes Ratings: B8									
	15	125	60	GP	6K	150	2/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	1/2hp	6K				
	-	250	60	1hp	6K				
DA w/wo suff. w/wo prefixes Ratings: C2									
	15	125	60	GP	6K	150	2/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	3/4hp	6K				
	-	250	60	1- 1/2hp	6K				
	2	48	DC	-	100K				
DA w/wo suff. w/wo prefixes Ratings: F1									
	12	250	50/60	GP	6K	150	2/M	-/-	-
	-	125	50/60	1/2hp	6K				
	-	250	50/60	1hp	6K				
	2	48	DC	-	100K				
DA w/wo suff. w/wo prefixes Ratings: F5									
	1	125	60	GP	6K	150	2/M	-/-	-
	1	30	DC	-	6K				
DA w/wo suff. w/wo prefixes Ratings: F6									
	1	125	60	GP	6K	150	2/M	-/-	-
DA w/wo suff. w/wo prefixes Ratings: L2									
	10	250	60	GP	6K	150	2/M	-/-	-
	2	48	DC	-	100K				
DA w/wo suff. w/wo prefixes Ratings: L8									

	30	277	60	GP	6K	150	2/M	-/-	-
	-	125	60	1hp	-				
	-	250	60	2hp	-				
DA101-xx-x-xx-xx-x-xx-x	10	250	60	1/2hp	6K	85	M/2	-/-	-
	16	125	60	1/3hp	6K				
DA102-J3-x-xx-xx-x-xx-x	10	250	60	1/2hp	6K	85	M/2	-/-	-
	16	125	60	1/3hp	6K				
DA102-J4-x-xx-xx-x-xx-x	16	125	60	1/3hp	6K	85	M/2	-/-	-
	10	250	60	1/2hp	6K				
DA102-J5-x-xx-xx-x-xx-x	10	250	60	1/2hp	-	85	M/2	-/-	-
	16	125	60	1/3hp	-				
DA102-xx-x-xx-xx-x-xx-x	10	250	60	1/2hp	6K	85	M/2	-/-	-
	16	125	60	1/3hp	6K				
DA103-xx-x-xx-xx-x-xx-x	10	250	60	1/2hp	6K	85	M/2	-/-	-
	16	125	60	1/3hp	6K				
DA800 to DA899 w/wo 0-9 w/wo prefixes w/wo suffixes Ratings: C2									
	15	125	60	GP	6K	150	2/M	-/-	-
	15	250	60	GP	6K				
	-	125	60	3/4hp	6K				
	-	250	60	1- 1/2hp	6K				
	2	48	DC	-	100K				
DA800 to DA899 w/wo 0-9 w/wo prefixes w/wo suffixes Ratings: C6									
	25	125	60	GP	6K	150	2/M	-/-	-
	25	250	60	GP	6K				
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				
DA800 to DA899 w/wo 0-9 w/wo prefixes w/wo suffixes Ratings: F1									
	12	250	50/60	GP	6K	150	2/M	-/-	-
	-	125	50/60	1/2hp	6K				
	-	250	50/60	1hp	6K				
	2	48	DC	-	100K				
DA800 to DA899 w/wo w/wo 0-9 w/wo prefixes w/wo suffixes Ratings: E1									
	25	125	60	GP	6K	150	2/M	-/-	-

	25	250	60	GP	6K				
	-	125	60	3/4hp	6K				
	-	250	60	1-1/2hp	6K				
DF52, DF62, or DF72 w/wo suffixes, f/b QA,QF									
	16	125	60	GP	6K	100	M/M	PP/-	3
	16	250	60	GP	6K				
	-	125	60	1/4hp	6K				
	-	250	60	1/2hp	6K				
	6	48	DC	-	6K				
	16	-	-	GP	6K				
	-	250	60	GP	6K				
	2	60	DC	-	6K				
	11	30	DC	-	10K				
DM14,DM21,DM22,DM24, KD21,KD22,RD21,RD22 w/suff.									
	3	125	60	GP	6K	65	M/M	-/-	-
	2	250	60	GP	6K				
DM54 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
DM61 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
DM62 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
DM64 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
DMX w/suffixes U1	10	125	DC	-	100K	150	M/M	-/-	-
DMX w/suffixes U3	10	125	DC	-	100K	150	M/M	-/-	-
	5	250	DC	-	100K				
E1,E2 f/b 01,03,05,07,08,11,13,15 w/wo suffixes									
	7.5	125	60	GP	6K	65	M/2	PP/-	-
	3	250	60	GP	6K				
E112 w/wo suff.	4	125	60	GP	6K	65	1/2	-/-	-
E221, E121 all w/wo suff.	1	125	60	GP	6K	65	M/2	PP/-	-
E3 f/b 01,03,05,07,08,11,13,15 w/wo suffixes									

	5	125	60	GP	6K	65	3/2	PP/-	-
	2	250	60	GP	6K				
	5	28	DC	-	6K				
ET01,ET21 w/wo suffixes	3	120	60	GP	6K	65	M/2	-/-	-
	1	250	60	GP	6K				
F Series w/wo suffixes	4	125	60	GP	6K	65	1,2/1-M	PP/-	-
	2	250	-	GP	6K				
	4	28	-	GP	6K				
F2U ww/o LT, f/b EE or OA ww/o +SP									
	0.4	125-250	60	R	6K	85	2/2	PP/-	-
F4U or F6U f/b EE or OA	0.4	125	60	R	6K	85	M/M	PP/-	-
G101	12	125	60	GP	6K	105	1/1	-/-	-
GW f/b O, SS, 5,6,7,8,9,14,f/b U-56, w/wo P w/wo suffixes									
	15	480	60	GP	6K	90	M/M	-/-	-
GW f/b O, SS, 5,6,7,8,9,14,f/b U-67, w/wo P w/wo suffixes									
	15	480	60	GP	6K	90	M/M	-/-	-
	-	125	60	1hp	6K				
GW f/b O, SS, 5,6,7,8,9,14,f/b U-91, w/wo P w/wo suffixes									
	25	250	60	GP	6K	90	M/M	-/-	-
GY Series w/wo suffixes	4	125	60	GP	6K	65	1,2/1-M	PP/-	-
	2	250	-	GP	6K				
	4	28	-	GP	6K				
H f/b 1,2 f/b 00-99 w/wo suffixes and N f/b 3-8 f/b 00-99 w/wo suffixes									
	12	125	60	GP	6K	65	M/M	PP/-	-
	6	250	60	GP	6K				
	1	125	DC	-	6K				
H5041 w/wo suff	13.5	125	60	GP	6K	65	M/M	PP/-	-
	6	250	60	GP	6K				
	1	125	DC	-	6K				
HB w/wo suffixes w/wo prefixes f/b "U13" "U13" = 100K wo U=6K									
	-	125-250	-	GP	100K	150	M/M	-/-	-
HB w/wo suffixes w/wo prefixes f/b "U18" "U18" = 100K wo U=6K									

	-	125-250	-	GP	100K	150	M/M	-/-	-
HB w/wo suffixes w/wo prefixes f/b "U2" "U2" = 100K wo U=6K									
	-	125-250	-	GP	100K	150	M/M	-/-	-
HB w/wo suffixes w/wo prefixes f/b "U39" "U39" = 100K wo U=6K									
	-	250	-	GP	100K	150	M/M	-/-	-
HB w/wo suffixes w/wo prefixes f/b "U63" = 100K wo U=6K									
	15	125-250	60	GP	100K	150	M/M	-/-	-
	15	480	60	GP	100K				
	-	125	60	1/8hp	100K				
	-	250	60	1/4hp	100K				
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U16" = 100K wo U=6K									
	22	125	60	GP	100K	150	M/M	-/-	-
	22	250	60	GP	100K				
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U19" = 100K wo U=6K									
	20	125	60	GP	100K	150	M/M	-/-	-
	20	250	60	GP	100K				
	-	125	60	1/2hp	100K				
	-	250	60	1hp	100K				
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U25" = 100K wo U=6K									
	22	125-277	60	GP	100K	150	M/M	-/-	-
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U26" = 100K wo U=6K									
	22	125-277	60	GP	100K	150	M/M	-/-	-
	-	125	60	1/4hp	100K				
	-	250	60	1/2hp	100K				
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U4" = 100K wo U=6K									
	1	125-250	60	GP	100K	150	M/M	-/-	-
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U40" = 100K wo U=6K									
	22	125	60	GP	100K	150	M/M	-/-	-
	22	277	60	GP	100K				
	15	480	60	GP	100K				

	-	125	60	1/4hp	100K				
	-	250	60	1/2hp	100K				
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U47" = 100K wo U=6K									
	15	250	60	GP	100K	150	M/M	-/-	-
	10	277	60	GP	100K				
	-	125	60	1/4hp	100K				
	-	250	60	1/2hp	100K				
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U54" = 100K wo U=6K									
	22	125-277	60	GP	100K	150	M/M	-/-	-
	15	480	60	GP	100K				
	-	125	60	1/4hp	100K				
	-	250-277	60	1/2hp	100K				
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U57" = 100K wo U=6K									
	22	125	60	GP	100K	150	M/M	-/-	-
	22	277	60	GP	100K				
	0.4	125	DC	-	100K				
	-	125	60	1/4hp	100K				
	-	250	60	1/2hp	100K				
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U58" = 100K wo U=6K									
	20	125	60	GP	100K	150	M/M	-/-	-
	20	250	60	GP	100K				
	20	480	60	GP	100K				
	0.25	250	DC	-	100K				
	0.5	125	DC	-	100K				
	-	125	60	1/8hp	100K				
	-	250	60	1/4hp	100K				
HB w/wo suffixes w/wo prefixes, KS w/suffixes, 22HB w/wo suffixes; Part No. f/b "U7" = 100K wo U=6K									
	15	125	60	GP	100K	150	M/M	-/-	-
	15	250	60	GP	100K				
HB, w/suffixes SBX,SXX w/suff. 24HB w/suffixes (F5)									
	1	125	60	GP	100K	150	M/M	-/-	-
HB,MB,MX,MXO,MXU w/suffixes SBX,SXX w/suff. 24HB w/suffixes (F5)									

	1	125	60	GP	100K	150	M/M	-/-	-
	1	30	DC	-	100K				
	1	125	60	GP	100K				
HB,MB,MX,MXO,MXU w/suffixes SBX,SXX w/suff. 24HB w/suffixes (U12)									
	20	125	60	GP	100K	150	M/M	-/-	-
	15	250	60	GP	100K				
	-	125	60	3/4hp	100K				
	-	250	60	3/4hp	100K				
	-	480	60	3/4hp	100K				
	-	480	60	3/4hp	100K				
HB,MB,MX,MXO,MXU w/suffixes SBX,SXX w/suff. 24HB w/suffixes (U44)									
	15	125	60	GP	100K	150	M/M	-/-	-
	15	250	60	GP	100K				
	15	480	60	GP	100K				
	0.2	250	DC	-	100K				
	0.4	125	DC	-	100K				
	-	125	60	1/8hp	100K				
	-	250	60	1/4hp	100K				
HB,MB,MX,MXO,MXU w/suffixes SBX,SXX w/suff. 24HB w/suffixes (U8)									
	15	125	60	GP	100K	150	M/M	-/-	-
	15	250	60	GP	100K				
	15	480	60	GP	100K				
	0.2	250	DC	-	100K				
	0.4	125	DC	-	100K				
HB,MB,MX,MXO,MXU w/suffixes SBX,SXX w/suff. 24HB w/suffixes (U9)									
	15	125	60	GP	100K	150	M/M	-/-	-
	15	250	60	GP	100K				
	15	480	60	GP	100K				
HG or 2HG f/b KJ,PC w/wo suff Ratings: C6									
	25	125	60	GP	6K	150	1/M	-/-	-
	25	250	60	GP	6K				
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				

HG or 2HG f/b KJ,PC w/wo suff Ratings: G1									
	25	125	60	GP	6K	150	1/M	-/-	-
	22	277	60	R	6K				
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				
HG or 2HG f/b KJ,PC w/wo suff Ratings: K2									
	20	125	60	GP	6K	150	1/M	-/-	-
	20	250	60	GP	6K				
	20	480	60	GP	6K				
HG or 2HG f/b KJ,PC w/wo suff Ratings: K9									
	30	125	60	GP	6K	150	1/M	-/-	-
	30	250	60	GP	6K				
	30	480	60	GP	6K				
HR w/suffixes w/wo prefixes Part No. f/b "U16" =100K wo U=6K									
	22	125	60	GP	100K	150	M/M	-/-	-
	22	250	60	GP	100K				
HR w/suffixes w/wo prefixes Part No. f/b "U25" =100K wo U=6K									
	22	125-277	60	GP	100K	150	M/M	-/-	-
HR w/suffixes w/wo prefixes Part No. f/b "U26" =100K wo U=6K									
	22	125-277	60	GP	100K	150	M/M	-/-	-
J102	6	125	60	GP	6K	65	1/2	-/-	Note 1
	3	250	60	GP	6K				
J112	10	125	60	GP	6K	65	1/2	-/-	-
	5	250	60	GP	6K				
JA01,JA03,JA05,JA07,JA08	2	125	60	GP	6K	65	1/2	-/-	Note 3
	1	250	60	GP	6K				
K101 w/wo suff	0.5	125	60	GP	6K	65	1/1	-/-	-
	0.25	250	60	GP	6K				
	0.5	125	DC	-	6K				
KD01 w/suffixes	2	250	60	GP	6K	65	M/M	-/-	-
KD02 w/suffixes	2	250	60	GP	6K	65	M/M	-/-	-
KD51 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2

	5	250	60	GP	6K				
KD52 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
KD61 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
KD62 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
KG w/wo Pref.and/or suff	25	125	60	GP	6K	150	1/M	-/-	-
	25	250	60	GP	6K				
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				
KM11 w/suff.	0.25	125	60	GP	6K	85	1/1	-/-	-
	0.25	125	DC	-	6K				
KM12 w/suff.	0.25	125	60	GP	6K	65	1/2	-/-	-
	0.25	125	DC	-	6K				
KS w/suffixes f/b "U13" "U13" = 100K wo U=6K									
	-	125-250	-	GP	100K	150	M/M	-/-	-
KS w/suffixes f/b "U18" "U18" = 100K wo U=6K									
	-	125-250	-	GP	100K	150	M/M	-/-	-
KS w/suffixes f/b "U2" "U2" = 100K wo U=6K									
	-	125-250	-	GP	100K	150	M/M	-/-	-
KS w/suffixes f/b "U39" "U39" = 100K wo U=6K									
	-	250	-	GP	100K	150	M/M	-/-	-
L f/b 11,13,15,17,18,21,23,25,27,28 and 52 f/b 11,13,15 all w/wo suff.									
	5	120	60	GP	6K	65	M/2	PP/-	-
	2	250	60	GP	6K				
L16 f/b 1,2 f/b 13-19 f/b 1,2 f/b MA,ML,MS,MV,SS,TS f/b WC,01,02,03,06,10,12 f/b B,G,Q									
	4	125	60	GP	6K	65	M/M	PP/-	-
	6	250	60	GP	6K				
L26 f/b 1,2 f/b 13-19 f/b 1,2 f/b MA,ML,MS,MV,SS,TS f/b WC,01,02,03,06,10,12 f/b B,G,Q									
	4	125	60	GP	6K	65	M/M	PP/-	-
	6	250	60	GP	6K				

L5302	2	125	60	GP	6K	65	M/M	-/-	-
	1	250	60	GP	6K				
L611 w/wo suffixes	6	125	60	GP	6K	65	2/M	PP/-	-
	3	250	60	GP	6K				
	0.5	125	DC	-	6K				
LC Series Rating: F5 (c)	1	125	60	GP	100K	85	1/M	-/-	-
	1	30	DC	-	100K				
LC Series Rating: L9 (c)	5	125	60	GP	100K	85	1/M	-/-	-
	5	250	60	GP	100K				
	-	125	60	1/3hp	100K				
	-	250	60	1/3hp	100K				
LC Series Rating: M1 (c)	10.1	125	60	GP	100K	85	1/M	-/-	-
	10.1	250	60	GP	100K				
	-	125	60	1/3hp	100K				
	-	250	60	1/3hp	100K				
LC Series Rating: M8 (c)	0.1	125	60	GP	100K	85	1/M	-/-	-
	0.1	30	DC	-	100K				
LC Series Rating: V6 (c)	5	125	60	GP	100K	85	1/M	-/-	-
	5	250	60	GP	100K				
	-	125	60	1/3hp	100K				
	-	250	60	1/3hp	100K				
LC Series Rating: V7 (c)	10.1	125	60	GP	100K	85	1/M	-/-	-
	10.1	250	60	GP	100K				
	-	125	60	1/3hp	100K				
	-	250	60	1/3hp	100K				
LC Series Rating: X1 (c)	1	125	60	GP	100K	85	1/M	-/-	-
	1	30	DC	-	100K				
LCA-Y, LCA-W, LCA-C	10	125	60	GP	6K	125	1/1	-/-	3
LCS 06 W, LCS 06 Y, LCS 06 C, LCS 06									
	6	125	60	GP	6K	105	1/M	-/-	-
	3	250	60	GP	6K				
LCS Series	5	125	60	GP	6K	120	1/1	-/-	-
	5	250	60	GP	6K				

	0.1	125	60	GP	6K				
	0.1	250	60	GP	6K				
	0.5	80	DC	R	6K				
LF-05A-080-L27-Q	5	125-250	60	GP	6K	85	1/1	-/-	-
	2	480	60	1/2hp	6K				
LF-05B-010-Pxx-Q-Y	5	125-250	60	GP	6K	85	1/1	-/-	-
	-	125	60	1/8hp	6K				
	-	250	60	1/4hp	6K				
LF-CC or CD-E2-A# or T#-H # represents 00-99									
	5	125-250	60	GP	6K	85	1/1	-/-	-
	2	480	60	1/2hp	6K				
LP f/b 01,02,21,22, f/b C1,C2,C3,f/b 1, f/b S2,T2, f/b 01,02,03, WC f/b D,L,N, f/b B,G,Q, f/b E									
	6	125	60	GP	6K	65	M/M	PP/-	-
	3	250	60	GP	6K				
	6	28	DC	-	6K				
LP f/b GD, GG, GH f/b E2 w/wo suffix									
	5	250	60	GP	6K	135	1/M	-/-	-
	2	480	60	GP	6K				
LP f/b GD, GG, GH f/b E3 w/wo suffix									
	10	250	60	GP	6K	135	1/M	-/-	-
LP f/b GD, GG, GH f/b F5 w/wo suffix									
	1	125	60	GP	6K	135	1/M	-/-	-
	1	30	DC	-	6K				
LP f/b GD, GG, GH f/b F6 w/wo suffix									
	1	125	60	GP	6K	135	1/2	-/-	-
MA f/b 00-10, f/b S1 w/wo suffixes									
	0.25	125	60	GP	6K	65	1/M	-/-	-
MB f/b 00-05, f/b S1 w/wo suffixes									
	0.25	125	60	GP	6K	65	2/M	PP/-	-
MB w/suffixes SBX,SXX w/suff. 24HB w/suffixes (U12)									
	1	125	60	GP	100K	150	M/M	-/-	-
MC f/b 00-12, f/b S1 w/wo suffixes									

	0.25	125	60	GP	6K	65	1/M	-/-	-
MD f/b 00-06, f/b S1 w/wo suffixes									
	0.25	125	60	GP	6K	65	2/M	PP/-	-
ME f/b 00-10, f/b S1 w/wo suffixes									
	0.25	125	60	GP	6K	65	1/M	-/-	-
MF f/b 00-05, f/b S1 w/wo suffixes									
	0.25	125	60	GP	6K	65	1/M	-/-	-
MG f/b 00-12, f/b S1 w/wo suffixes									
	0.25	125	60	GP	6K	65	1/M	-/-	-
MH f/b 00-06, f/b S1 w/wo suffixes									
	0.25	125	60	GP	6K	65	2/M	PP/-	-
MMGG f/b D1, E2, F5, F6 f/b ALS1, ALS2, AWS1, AWS2, D0, L0, L2, P0, W0, W2 f/b A, C, S, T w/wo suffixes Rating: F5									
	1	125	60	GP	6K	150	1/2	-/-	-
	1	30	DC	-	6K				
MMGG f/b D1, E2, F5, F6 f/b ALS1, ALS2, AWS1, AWS2, D0, L0, L2, P0, W0, W2 f/b A, C, S, T w/wo suffixes Rating: F6									
	1	125	60	GP	6K	150	1/2	-/-	-
MMGG f/b D1, E2, F5, F6 f/b ALS1, ALS2, AWS1, AWS2, D0, L0, L2, P0, W0, W2 f/b A, C, S, T w/wo suffixes Rating: F82									
	1	120	60	GP	6K	150	1/2	-/-	-
	0.05	28	DC	-	6K				
MMGG f/b D1, E2, F5, F6 f/b ALS1, ALS2, AWS1, AWS2, D0, L0, L2, P0, W0, W2 f/b A, C, S, T w/wo suffixes Rating: U28									
	7	250	60	GP	-	-	-	-/-	-
MMGG f/b D1, E2, F5, F6 f/b ALS1, ALS2, AWS1, AWS2, D0, L0, L2, P0, W0, W2 f/b A, C, S, T w/wo suffixes Rating: U38									
	5	120	60	GP	6K	150	1/2	-/-	-
MS-105	5	125	50	R	6K	85	1/2	-/-	-
	3	250	50	R	6K				
MS-205	5	125	50	R	6K	85	1/2	-/-	-
	3	250	50	R	6K				
MX, w/suffixes SBX,SXX w/suff. 24HB w/suffixes (U44)									
	1	125	60	GP	100K	150	M/M	-/-	-
MXO w/suffixes SBX,SXX w/suff. 24HB w/suffixes (U9)									

	1	125	60	GP	100K	150	M/M	-/-	-
MXOA w/suffixes HL,KL,KWL all w/wo prefixes and suffixes Ratings: B4									
	20	125	60	GP	6K	150	1/M	-/-	-
	20	250	60	GP	6K				
	20	480	60	GP	6K				
	0.5	125	DC	-	6K				
	0.25	250	DC	-	6K				
MXOA w/suffixes HL,KL,KWL all w/wo prefixes and suffixes Ratings: C3									
	20	125	60	GP	6K	150	1/M	-/-	-
	20	250	60	GP	6K				
	20	480	60	GP	6K				
	10	125	60	L	6K				
	0.5	125	DC	-	6K				
	0.25	250	DC	-	6K				
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				
MXOA w/suffixes HL,KL,KWL all w/wo prefixes and suffixes Ratings: C4									
	20	125-250	60	GP	6K	150	1/M	-/-	-
	20	480	60	GP	6K				
	0.5	125	DC	-	6K				
	0.25	250	DC	-	6K				
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				
MXOA w/suffixes HL,KL,KWL all w/wo prefixes and suffixes Ratings: C5									
	20	125	60	GP	-	105	M/M	-/-	-
	20	250	60	GP	-				
	20	480	60	GP	-				
	-	125	60	1hp	-				
	-	250	60	2hp	-				
N1, N2 f/b 00-99 w/wo suffixes									
	4	125	60	GP	6K	65	M/M	PP/-	-
	4	28	DC	-	6K				
NE18 f/b -1a, -1r, -1u, w/wo pref F4U, F2U									

	6	250	60	GP	6K	70	1/1 or 2	-/A	-
	8	125	60	GP	6K				
	0.5	24	DC	-	6K				
NE18 f/b -2a, -2r, -2u, w/wo pref F4U, F2U									
	6	250	60	GP	6K	70	2/ 1 or 2	PP/D	-
	8	125	60	GP	6K				
	0.5	24	DC	-	6K				
NE18CT11 f/b -2a, w/wo pref F4U, F2U									
	6	250	60	GP	6K	70	2/1	PP/D	-
	8	125	60	GP	6K				
	0.5	24	DC	-	6K				
NS f/b [M1] [M1] = [f/b EB, ED f/b H7, J1, K5, K8, J9 w/wo V w/wo A, T f/b 4, 40 f/b W, Y w/wo suffixes Rating: U70]									
	-	277	-	GP	6K	75	1/1	-/-	-
NS f/b [M2] [M2] = [f/b EB, ED f/b H7, J1, K5, K8, J9 w/wo V w/wo A, T f/b 4, 40 f/b W, Y w/wo suffixes Rating: U73]									
	-	277	-	GP	6K	75	1/1	-/-	-
NS f/b [M3] [M3] = [f/b EB, ED f/b H7, J1, K5, K8, J9 w/wo V w/wo A, T f/b 4, 40 f/b W, Y w/wo suffixes Rating: U86]									
	-	277	-	GP	6K	75	1/1	-/-	-
NS f/b [M4] [M4] = [f/b EB, ED f/b H7, J1, K5, K8, J9 w/wo V w/wo A, T f/b 4, 40 f/b W, Y w/wo suffixes Rating: U89]									
	-	277	-	GP	6K	75	1/1	-/-	-
NS f/b [M5] [M5] = [f/b EB, ED f/b H7, J1, K5, K8, J9 w/wo V w/wo A, T f/b 4, 40 f/b W, Y w/wo suffixes Rating: U81]									
	-	277	-	GP	6K	75	1/1	-/-	-
P Series w/wo suffixes	4	125	60	GP	6K	65	1,2/1,2	PP/-	-
	2	250	-	GP	6K				
	4	28	-	GP	6K				
P10,P20 f/b 0, 1 f/b AF, 13, 1U w/wo suffixes									
	4	125	60	GP	6K	65	M/M	PP/-	-
	1	250	60	GP	6K				
PF Series w/wo suff.	4	125	60	GP	6K	65	M/M	-/-	-
	2	250	60	GP	6K				
PM Series w/wo suff.	4	125	60	GP	6K	65	1/1	-/-	-

	2	250	60	GP	6K				
	4	28	DC	-	6K				
	4	28	60	GP	6K				
PR3-0-X-X-XXI	6	250	60	GP	6K	65	1/1	-/-	2, Note 2
PR3-2-X-X-XXI	6	250	60	GP	6K	65	2/1	-/-	2, Note 2
PS101,PS201	4	125	60	GP	6K	105	M/2	-/-	-
	2	250	60	GP	6K				
PS103, PS203	4	125	60	GP	6K	105	M/2	PP/-	-
	2	250	60	GP	6K				
PS1S1, PS1S3	4	125	60	GP	6K	65	M/2	-/-	-
	2	250	60	GP	6K				
PSE01	3	125	60	GP	6K	-	M/2	-/-	-
	1.5	250	60	GP	6K				
PST01	2	125	60	GP	6K	65	1/2	-/-	-
R 5115	5	125	60	GP	6K	95	1/M	-/-	-
	2.5	250	60	GP	6K				
	0.5	125	DC	-	6K				
R f/b 100-109,200-205 w/wo suffixes									
	5	125	60	GP	6K	65	M/M	PP/-	-
	2.5	250	60	GP	6K				
	0.5	125	DC	-	6K				
R13-72, f/b A, B, C, D or I, f/b -01or -05									
	16	125	60	GP	6K	85	1/1 or 1/2	-/A	Note 12
	10	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/2hp	6K				
RD01 w/suffixes	2	250	60	GP	6K	65	M/M	-/-	-
RD02 w/suffixes	2	250	60	GP	6K	65	M/M	-/-	-
RD51 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
RD52 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				

RD61 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
RD62 w/suffixes	10	125	60	GP	6K	65	M/M	-/-	2
	5	250	60	GP	6K				
RU f/b S, T,f/b PB, f/b C3,w/wo suffix W									
	20	125	60	GP	6K	85	1/1	-/-	-
	20	250	60	GP	6K				
	20	480	60	GP	6K				
	10	125	60	L	6K				
	0.5	125	DC	-	6K				
	0.25	250	DC	-	6K				
	-	125	60	1hp	6K				
	-	250	60	2hp	6K				
RU f/b S, T,f/b PB,KA, f/b B5,w/wo suffix C									
	20	125	60	GP	6K	150	1/2	-/-	-
	20	250	60	GP	6K				
	20	480	60	GP	6K				
	0.5	125	DC	-	6K				
	0.25	250	DC	-	6K				
	-	125	60	1/2hp	6K				
	-	250	60	1hp	6K				
S1,S2 f/b 0-3 f/b 1-3, w/wo suffixes									
	6	125-250	60	GP	6K	85	M/M	PP/-	-
	1	125	DC	-	6K				
S5,S6 f/b 0-3 f/b 1-3, w/wo suffixes									
	12	125	60	GP	6K	85	M/M	PP/-	-
	6	250	60	GP	6K				
	1	125	DC	-	6K				
S7,S8 f/b 0-3 f/b 1-3, w/wo suffixes									
	15	125	60	GP	6K	85	M/M	PP/-	-
	6	250	60	GP	6K				
SS-12J08	4	125	50	R	6K	65	1/2	-/-	Note 3C
	2	250	50	R	6K				

SW-1 f/b 2 or 3 f/b A65N-A f/b 01 or 02 may be f/b BK, BI or AK									
	6.5	125	60	GP	6K	65	1/2	-/A	-
T1 f/b 147A,135, 135A Rating: U45									
	22	277	60	GP	6K	-	1/1	-/-	-
T10 f/b 2,3,5,7,8 and ET f/b 0,2 f/b 3,5,7,8 ET02,ET24 all w/wo suffixes									
	2	120	60	GP	6K	65	M/M	-/-	-
T101 w/suff.	3	120	60	GP	6K	65	M/2	-/-	-
T20 f/b 2,3,5,7,8 and ET f/b 0,2 f/b 3,5,7,8 ET02,ET24 all w/wo suffixes									
	2	120	60	GP	6K	65	M/M	-/-	-
T201 w/suff.	3	120	60	GP	6K	65	2/2	-/-	-
T211 w/suff.	2	120	60	GP	6K	65	2/2	-/-	-
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b F5 with or without suffixes f/b C,W,Y									
	1	125	60	GP	66K	75	1/M	-/-	-
	1	30	DC	-	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b F6 with or without suffixes f/b C,W,Y									
	1	125	60	GP	66K	75	1/M	-/-	-
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b H5 with or without suffixes f/b C,W,Y									
	3	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/10hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b H6 with or without suffixes f/b C,W,Y									
	3	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/10hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b H7 with or without suffixes f/b C,W,Y									
	3	277	60	GP	66K	75	1/M	-/-	-
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b H8 with or without suffixes f/b C,W,Y									
	5	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/10hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b H9 with or without suffixes f/b C,W,Y									
	5	277	60	GP	66K	75	1/M	-/-	-
	-	250	60	1/10hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b J1 with or without suffixes f/b C,W,Y									
	5	277	60	GP	66K	75	1/M	-/-	-

	5	125	60	L	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b J2 with or without suffixes f/b C,W,Y									
	21	277	60	GP	66K	75	1/M	-/-	-
	-	125	60	1hp	66K				
	-	250	60	2hp	66K				
	5	125	60	L	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b J3 with or without suffixes f/b C,W,Y									
	21	277	60	GP	66K	75	1/M	-/-	-
	-	125	60	1hp	66K				
	-	250	60	2hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b J4 with or without suffixes f/b C,W,Y									
	21	277	60	GP	66K	75	1/M	-/-	-
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b J6 with or without suffixes f/b C,W,Y									
	15	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/2hp	66K				
	5	125	60	L	66K				
	0.25	250	DC	-	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b J7 with or without suffixes f/b C,W,Y									
	15	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/2hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b J8 with or without suffixes f/b C,W,Y									
	15	277	60	GP	66K	75	1/M	-/-	-
	-	250	60	1/2hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b J9 with or without suffixes f/b C,W,Y									
	15	277	60	GP	66K	75	1/M	-/-	-
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b K3 with or without suffixes f/b C,W,Y									
	10	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/3hp	66K				
	0.5	125	DC	-	66K				
	0.25	250	DC	-	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b K4 with or without suffixes f/b C,W,Y									
	10	277	60	GP	66K	75	1/M	-/-	-

	-	125-250	60	1/3hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b K5 with or without suffixes f/b C,W,Y									
	10	277	60	GP	66K	75	1/M	-/-	-
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b K6 with or without suffixes f/b C,W,Y									
	11	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/3hp	66K				
	0.5	125	DC	-	66K				
	0.25	250	DC	-	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b K7 with or without suffixes f/b C,W,Y									
	11	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/3hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b K8 with or without suffixes f/b C,W,Y									
	11	277	60	GP	66K	75	1/M	-/-	-
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b L1 with or without suffixes f/b C,W,Y									
	25	125	60	GP	66K	75	1/M	-/-	-
	25	277	60	GP	66K				
	-	125	60	1-1/2hp	66K				
	-	250	60	2hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b M4 with or without suffixes f/b C,W,Y									
	5	277	60	GP	66K	75	1/M	-/-	-
	5	480	60	GP	66K				
	-	125	60	1/3hp	66K				
	-	250	60	1/3hp	66K				
	0.5	125	DC	-	66K				
	0.25	250	DC	-	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b M5 with or without suffixes f/b C,W,Y									
	21	277	60	GP	66K	75	1/M	-/-	-
	-	125	60	1-1/2hp	66K				
	-	250	60	2hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b M8 with or without suffixes f/b C,W,Y									

	0.1	125	60	GP	66K	75	1/M	-/-	-
	0.1	30	DC	-	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b V2 with or without suffixes f/b C,W,Y									
	5	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/10hp	66K				
TF f/b CC,CD,CF,CG,CJ,EC,EE,f/b V3 with or without suffixes f/b C,W,Y									
	11	277	60	GP	66K	75	1/M	-/-	-
	-	125-250	60	1/3hp	66K				
	0.5	125	DC	-	66K				
	0.25	250	DC	-	66K				
TF f/b [M1] [M1] = [f/b CC,CD,CF,CG,CJ,EC,EE,f/b V1 with or without suffixes f/b C,W,Y]									
	-	125	-	GP	66K	75	1/M	-/-	-
TF f/b [M2] [M2] = [f/b CC,CD,CF,CG,CJ,EC,EE,f/b V4 with or without suffixes f/b C,W,Y]									
	-	125	-	GP	66K	75	1/M	-/-	-
TH f/b 01, 31, 42, 51, 52, 61-67, 71, 72, 81, 82 w/wo P f/b 1, 2, A-K f/b 2-8 f/b 1-4 f/b B, C, G, O, R, S, W, Y Rating: U38									
	-	250	-	GP	6K	65	1/M	-/-	-
TH25 f/b F, F1, L, W f/b 9 f/b, 1, 2, 5 f/b 1,2 Ratings: U64									
	1	250	60	GP	6K	65	M/2	PP/-	-
TH25 w/wo P f/b F, F1, L, W f/b 9 f/b, 1, 2, 5 f/b 1, 2 Ratings: U38									
	5	250	60	GP	6K	65	M/2	PP/-	-
TM f/b CF or CG f/b Rating Codes E2, f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,40A (except F5 & F6 Rating Codes), 60,06 f/b C,W or Y									
	5	250	60	GP	6K	150	1/M	-/-	-
	2	480	60	GP	6K				
TM f/b CF or CG f/b Rating Codes E3, f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,40A (except F5 & F6 Rating Codes), 60,06 f/b C,W or Y									
	10	250	60	GP	6K	150	1/M	-/-	-
TM f/b CF or CG f/b Rating Codes F5, f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,40A (except F5 & F6 Rating Codes), 60,06 f/b C,W or Y									
	1	125	60	GP	6K	150	1/M	-/-	-
	1	30	DC	-	6K				
TM f/b CF or CG f/b Rating Codes F6, f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,40A (except F5 & F6 Rating Codes), 60,06 f/b C,W or Y									

	1	125	60	GP	6K	150	1/M	-/-	-
TM f/b CJ f/b Rating Codes E2 f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,4A (except F5 F6 Rating Codes) 60,06 f/b C,W or Y									
	5	250	60	GP	6K	150	1/M	-/-	-
	2	480	60	GP	6K				
TM f/b CJ f/b Rating Codes E3 f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,4A (except F5 F6 Rating Codes) 60,06 f/b C,W or Y									
	10	250	60	GP	6K	150	1/M	-/-	-
TM f/b CJ f/b Rating Codes E7 f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,4A (except F5 F6 Rating Codes) 60,06 f/b C,W or Y									
	10	250	60	GP	6K	150	1/M	-/-	-
TM f/b CJ f/b Rating Codes F5 f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,4A (except F5 F6 Rating Codes) 60,06 f/b C,W or Y									
	1	125	60	GP	6K	150	1/M	-/-	-
	1	30	DC	-	6K				
TM f/b CJ f/b Rating Codes F6 f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,4A (except F5 F6 Rating Codes) 60,06 f/b C,W or Y									
	1	125	60	GP	6K	150	1/M	-/-	-
TM f/b CJ f/b Rating Codes H3 f/b 4 suffixes f/b 10,1A (except F5 & F6 Rating Codes), 40,4A (except F5 F6 Rating Codes) 60,06 f/b C,W or Y									
	5	250	60	GP	6K	150	1/M	-/-	-
	-	125	60	1/6hp	6K				
	-	250	60	1/6hp	6K				
TM-CF-D6 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 40A (except F5 & F6 Rating Codes), 60, 06 f/b C,W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CF-D7 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 40A (except F5 & F6 Rating Codes), 60, 06 f/b C,W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CF-H3 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 40A (except F5 & F6 Rating Codes), 60, 06 f/b C,W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CG-D6 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 40A (except F5 & F6 Rating Codes), 60, 06 f/b C,W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-

TM-CG-D7 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 40A (except F5 & F6 Rating Codes), 60, 06 f/b C,W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CG-H3 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 40A (except F5 & F6 Rating Codes), 60, 06 f/b C,W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CJ-D3 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 4A (except F5 F6 Rating Codes) 60, 06 f/b C, W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CJ-D4 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 4A (except F5 F6 Rating Codes) 60, 06 f/b C, W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CJ-D6 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 4A (except F5 F6 Rating Codes) 60, 06 f/b C, W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CJ-D7 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 4A (except F5 F6 Rating Codes) 60, 06 f/b C, W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CJ-G6 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 4A (except F5 F6 Rating Codes) 60, 06 f/b C, W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CJ-G7 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 4A (except F5 F6 Rating Codes) 60, 06 f/b C, W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TM-CJ-G8 f/b 4 suffixes f/b 10, 1A (except F5 & F6 Rating Codes), 40, 4A (except F5 F6 Rating Codes) 60, 06 f/b C, W or Y									
	-	125-250	-	GP	6K	150	1/M	-/-	-
TP or EP f/b 11,12,21 w/suff. (b)									
	1	120	60	GP	6K	65	M/M	-/-	-
TR f/b CF, CG, CJ f/b E2 w/wo suff.									
	5	250	60	GP	6K	204	1/M	-/-	-
	2	480	DC	-	6K				

TR f/b CF, CG, CJ f/b F5 w/wo suff.									
	1	125	60	GP	6K	204	1/M	-/-	-
	1	30	DC	-	6K				
TR f/b CF, CG, CJ f/b F6 w/wo suff.									
	1	125	60	GP	6K	204	1/M	-/-	-
TR f/b CF, CG, CJ f/b H3 w/wo suff.									
	5	250	60	GP	6K	204	1/M	-/-	-
TR f/b CF, CG, CJ f/b L6 w/wo suff.									
	10.1	125	60	GP	6K	204	1/M	-/-	-
	10.1	250	60	GP	6K				
	-	125	60	1/3hp	6K				
	-	250	60	1/3hp	6K				
	-	125	DC	1/2hp	6K				
	-	250	DC	1/4hp	6K				
TS01 w/wo suffixes	3	120	60	GP	6K	65	1/M	-/-	-
TS02, TS03 w/wo suffixes	1	120	60	GP	6K	65	1/2	-/-	-
U f/b 13,15,17,18,19,21,23,25, 27,28,29,31, 33,35,37,38, 39,41,43,45, 47,48,49,211, 213,215,318,411, 413,415 and Z f/b 13,15,17, (Report Date: 1971-01-27) 18,19 and 7103, 7203, 7343, 7331 all w/wo suffixes									
	5	125-250	60	GP	6K	105	M/M	PP/-	-
	2	125-250	60	GP	6K				
U11, U21, 7243 w/wo suffixes									
	5	120	60	GP	6K	105	M/2	-/-	-
	2	250	60	GP	6K				
U201 w/wo suffixes	6	120	60	GP	6K	105	2/2	-/-	-
	2	250	60	GP	6K				
U321	5	120	60	GP	6K	105	3/2	PP/-	-
U8 f/b 11, 21, 31, 41	1	120	60	GP	6K	65	M/2	PP/-	-
	1	120	60	GP	10K				
V f/b 1,2,7,8 f/b 01,02	10.1	125	60	GP	6K	85	M/M	PP/-	-
	5	250	60	GP	6K				
	4	28	DC	-	6K				
W f/b 100, 101, 200, 201 f/b 13, 1C, 1V w/suffix f/b 82, AA w/suffix W100AB, w/suffix									
	4	125	60	GP	6K	65	M/M	PP/-	A1

	2	250	60	GP	6K				
WL,WLU w.suff. MXOA w/suffixes U4									
	15	125-250	60	GP	100K	150	M/M	-/-	-
WL,WLU w.suff. MXOA w/suffixes U5									
	15	125	60	GP	100K	150	M/M	-/-	-
	15	250	60	GP	100K				
	0.5	125	DC	-	100K				
	0.25	250	DC	-	100K				
WL,WLU w.suff. MXOA w/suffixes U52									
	15	125-250	60	GP	100K	150	M/M	-/-	-
	15	480	60	GP	100K				
	0.5	125	DC	-	100K				
	0.25	250	DC	-	100K				
WL,WLU w.suff. MXOA w/suffixes U53									
	15	125-250	60	GP	100K	150	M/M	-/-	-
	15	480	60	GP	100K				
	0.5	125	DC	-	100K				
	0.25	250	DC	-	100K				
	-	125	60	1/4hp	100K				
	-	250	60	1/2hp	100K				
WL,WLU w.suff. MXOA w/suffixes U6									
	15	125	60	GP	100K	150	M/M	-/-	-
	15	250	60	GP	100K				
	0.5	125	DC	-	100K				
	0.25	250	DC	-	100K				
	-	125	60	1/2hp	100K				
	-	250	60	1hp	100K				
WL,WLU w.suff. MXOA w/suffixes U7									
	15	125	60	GP	100K	150	M/M	-/-	-
	15	250	60	GP	100K				
	15	480	60	GP	100K				
Y Series w/wo suffixes	4	125	60	GP	6K	65	1,2/1-M	PP/-	-

	2	250	-	GP	6K				
	4	28	-	GP	6K				
YF f/b 00,01,20,21,45,90 f/b -13,-1C,-1V f/b 2,3 f/b C f/b 2,3 f/b C f/b 2, 8,F f/b 01,02, 03,07,WC f/b N f/b B,Q,G									
	4	125	60	GP	6K	65	M/M	PP/-	-
	2	250	60	GP	6K				
	4	28	DC	-	6K				
YM0613 f/b 2C,3C f/b 2,5,F f/b 05,WC f/b N,Q									
	4	125	60	GP	6K	65	1/1	-/-	Note 5
	2	250	60	GP	6K				
	4	28	DC	-	6K				
YM061U f/b 2C,3C f/b 2,5,F f/b 05,WC f/b N,Q									
	4	125	60	GP	6K	65	1/1	-/-	Note 5
	2	250	60	GP	6K				
	4	28	DC	-	6K				
Z f/b 1,2 f/b 01,03,05,07,08,09,11,13,15 all w/wo suff.									
	3	125	60	GP	6K	105	M/2	-/-	-
	1.5	250	60	GP	6K				

(a) - For endurance, 100 K for U77.

(b) - for temperature, 140 C fro EP11/ EP12.

(c) - LC Series for ratings U50, U108 may be f/b "U" ; "U" = 100K, w/o "U" = 6K.

+ - Followed by 7 or 8

A2 - The construction applied for the rating 16 A and 14 A is different. The spring with 12.5 mm long is used for 14/10 A, 125/250 V ac; 1/3 hp, 125 V ac; 1/2 hp, 250 V ac. The spring with 13.3 mm long is used for 16/10 A, 125/250 V ac; 1/3 hp, 125 V ac; 1/2 hp, 250 V ac.

A3 - Waterproof should be evaluated for compliance with the end-use product Standard.

Note 1 - Cat. No. J102 is intended for use on printed circuit boards and the suitability of the mounting of this device to the board should be determined in the end use.

Note 10 - Heating test was conducted at ambient temperature of 85 deg C with measured maximum temperature of 41.4 deg C on terminals, the suitability of wire conductors using on the switches terminals shall be determined in end-product applications.

Note 11 - UL61058-1 - The switches shall be enclosed with a suitable enclosure, and the acceptability shall be determined in end-product applications.

Note 12 - UL61058-1 - The switches are provided with solder type terminals that are suitable for soldering by hand with a soldering iron at 350 degree C. Also, the solder type terminals are suitable for soldering by solder bath at 235 degree C.

Note 13 - UL61058-1 - The tests were conducted with wire size No. 18 AWG stranded copper wire only.

Note 14 - UL61058-1 - The switches provide with solder terminals that intended to connect prepared conductor of No.18 AWG stranded copper wire only.

Note 15 - UL61058-1 - The switch is provided with Basic Insulation. The end use evaluation shall ensure all switch parts shall not be exposed to operator accessible.

Note 16 - When mounted in accordance with the manufactures instruction, this switch gets a protection degree of IP 67 with mounting enclosure opening OD 6 mm as mounting means. Internal parts were not evaluated for IP ratings and must be considered in the end product.

Note 17 - The Switch body is installed inside of end product and considered no accessible parts.

Note 18 - Heating test was conducted at ambient temperature of 85 deg C with measured maximum temperature of 97.7 deg C on terminals, the suitability of wire conductors using on the switches terminals shall be determined in end-product applications.

Note 19 - Termination other than solder connection, should be evaluated for compliance with the end-use product standard.

Note 1B - UL61058-1 - The Switch body is installed inside of end product; only consider the Rocker as accessible parts.

Note 1C - UL61058-1 - Heating test was conducted at ambient temperature of 85 deg C with measured maximum temperature of 113.2 deg C on terminals, the suitability of wire conductors using on the switches terminals shall be determined in end-product applications.

Note 2 - Terminations other than solder connections should be evaluated for compliance with the end-use product standard.

Note 20 - The switches were not evaluated for protection against splashing water - IPX4.

Note 21 - The safety function of the lock-off device was not evaluated. Suitability of the lock-off function shall be determined in the end-use application.

Note 22 - UL61058-1 - The switches are provided with solder type terminals that are suitable for soldering by hand with a soldering iron at 350 degree C. Also, the solder type terminals are suitable for soldering by solder bath at 260 degree C.

Note 23 - Switches without the 30°C/6K rating did not meet TE2 (DV) or 30°C rise after 6000 endurance cycles. The acceptability of switches intended for use in end products certified to North American standards, not harmonized to IEC standards, shall be determined by the end-use product standard.

Note 3 - The switches are provided with terminals for printed circuit board connection. These terminals have not been investigated. The suitability of these terminals should be determined in the end-use application.

Note 3A - The Switch body is installed inside of end product and consider the mounting surface and Knob is the accessible part.

Note 3B - IP 40 testing was completed on the complete switch without an end product enclosure. The switch gasket (seal) to the end product enclosure is evaluated in the end product testing.

Note 3C - The switch has openings in the housing adjacent to arcing parts. Caution is needed if the end-use application involves combustible dust or adjacent combustible materials that could be ignited by switch arcing.

Note 4 - Cat. No. AQ34A-W has been evaluated for a rating of 5 FLA, 480 Vac, 10 LRA, 480 Vac in accordance with the Standard for Temperature Indicating and Regulating Equipment (UL 873).



Note 5 - The nonstandard quick-connect terminals have not been evaluated. They should be evaluated in the end use.

Note 6 - UL61058-1 - When mounted in accordance with the manufactures instruction, this switch gets a protection degree of IP 40.

Note 7 - UL61058-1 - The switch is to be employed in an end use product providing an enclosure or insulating barrier that provides Reinforced or Double Insulation over the front and rear switch enclosure Surfaces.

Note 8 - UL61058-1 - The terminals have been evaluated for use with 26 AWG Rigid stranded conductors.

Note 9 - UL61058-1 - The Switch body is installed inside of end product and considered no accessible parts.

Marking: Company name or tradename "C & K Unimax", "P/", "PRIME SOURCE", "PS", "PSL" or trademark  , catalog, model or part number, electrical ratings and the Recognized Component Mark for Canada,  on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2019-10-15

Der Umstand, dass der Name oder das Produkt eines Unternehmens in dieser Datenbank aufgeführt ist, garantiert nicht, dass die Herstellung der jeweiligen Produkte dem Follow-Up-Service von UL unterliegt. Nur Produkte mit UL-Zeichen gelten als zertifiziert und sind vom Follow-Up-Service von UL abgedeckt. Prüfen Sie daher stets, ob ein Produkt das UL-Zeichen trägt.

UL gestattet die Weiterverwendung der im Online-Zertifizierungsverzeichnis enthaltenen Materialien unter den folgenden Bedingungen: 1. Alle Anleitungen, Baugruppen, Konstruktionen, Designs, Systeme und/oder Zertifizierungen (Dateien) müssen vollständig und auf nicht irreführende Weise ohne Manipulation der Daten (oder Zeichnungen) dargestellt werden. 2. Bei Weiterverwendung von Materialien muss der Vermerk „Aus dem Online-Zertifizierungsverzeichnis mit Genehmigung von UL nachgedruckt“ stets mit angegeben werden. Darüber hinaus muss das nachgedruckte Material einen Urheberrechtsvermerk in folgendem Format enthalten: "© 2020 UL LLC"